G3W-SUITE Documentation

Release dev

GIS3W Team

Jan 24, 2024

INSTALLATION AND DEPLOY

1	Raw	installation 3
	1.1	Install required packages
	1.2	Install QGIS Server
	1.3	Installation of node.js and Yarn 4
	1.4	Create virtualenv
	1.5	Virtualenv creation
	1.6	Install G3W-SUITE
	1.7	Deploy G3W-SUITE
	1.8	Manual installation steps
	1.9	Continuous integration testing
2	Dock	erization
	2.1	Deploy
	2.2	G3W-SUITE with consumer image 10
	2.3	Builds
	2.4	Setups
	2.5	Front-end App
	2.6	Style customization
	2.7	Performances optimization
	2.8	PostgreSQL administration
	2.9	Portainer usage
3	Dock	er environment variables 15
	3.1	Requirements variables
	3.2	Other not required settings
4	Setti	1gs 19
	4.1	Base settings
	4.2	Database logging
	4.3	Frontend portal setting
	4.4	General layout settings
	4.5	Client layout settings
	4.6	Editing settings
	4.7	Caching settings
	4.8	Filemanger settings
	4.9	Qplotly settings
	4.10	Openrouteservice settings
	4.11	Vendors settings
	4.12	Google reCAPTCHA
	4.13	Registration

	4.14 Caching	28				
5	Introduction	29				
	5.1 Version 5.2 Main contributors	30 30				
6	Technological infrastructure	31				
7	Management and organization of geographic data and QGIS projects					
	 7.1 Data on DB Server	35 36				
8	Hierarchical organization of WebGis services and types of Users (roles)	39				
	8.1 Types of Users (Roles)	40				
	8.2 Hierarchical organization of contents	40				
	 8.3 Accessed the File Manager tool 8.4 Summary table of access/administration policies 	42 43				
9	QGIS: project settings	45				
	9.1 Project property	45				
	9.2 General aspects	49				
	9.3 Layers properties	50				
	9.5 Performances optimization	56				
10	G3W-FRONTEND: the front end portal	57				
	10.1 The login portal sessions	57				
11	G3W-ADMIN: the Administration panel	61				
	11.1 Description of the interface	61				
	11.2 Front end portal customization	62				
	11.3 Users and Users Groups management	66 60				
	11.4 Macro Cartographic Groups	71				
	11.6 Publication of new WebGis services	80				
	11.7 Update/ Manage WebGis services	83				
	11.8 Widget management	87				
	11.9 Multilinguage	97				
12	2 G3W-CLIENT: the cartographic client	99				
	12.1 Generic aspects	99				
	12.2 Navigation and interaction with the map	101				
	12.5 Time series 12.4 Time series	118				
13	Editing on line	110				
13	13.1 Activation and configuration	119				
	13.2 Online editing tools at cartographic client level	131				
14	Introduction	139				
15	5 Download demo data	141				
	15.1 Modify the QGIS project title	143				
16	Access the online service	145				

17	7 Publish the QGIS project as a WebGis service 1					
	17.1 QGIS project	148				
	17.2 ACL Users	148				
	17.3 Default base layer	149				
	17.4 Description data	149				
	17.5 Options and actions	149				
18	3 Update the published WebGis service 15					
19	Activation of additional functions	155				
19	Activation of additional functions 19.1 Widget management	155 155				
19	Activation of additional functions19.1Widget management19.2Search widget creation	155 155 157				
19	Activation of additional functions19.1Widget management19.2Search widget creation19.3Plots widget	155 155 157 159				
19 20	Activation of additional functions 19.1 Widget management	 155 155 157 159 163 				

G3W-SUITE is a frame-work, based on Django and written in Python language, which allows to manage in an integrated way the different components of QGIS for the realization of its own Geographic Information System and for the publication on WebGis of its own projects in a simple and intuitive way.

G3W-SUITE is entirely based on tested Open Source software components built around QGIS:

- QGIS Desktop: for cartographic data management, editing and realization of high quality graphic projects
- QGIS Server: for the publication of QGIS projects as OGC services

The current development policy provides for the compatibility of the G3W-SUITE application only with the latest LTR version of QGIS

The current release (3.7) is compatible with QGIS 3.28 LTR (Server and Desktop).

G3W-SUITE is a modular client-server application for the publication and management of QGIS cartographic projects, consisting of 3 components:

- G3W-ADMIN: Administration component (project management, ACL, OGC proxy server, API rest server)
- G3W-CLIENT: Cartographic client for consultation and interaction with OGC services
- Front-end geographic portal: access to information, thematic groups and WebGis services

Through the web interface of the G3W-SUITE framework it is possible to:

- publish QGIS projects directly on WebGis in a structured way
- organize webgis services in thematic-functional containers of various levels
- manage users and groups of users by defining each of them different functional roles
- · create and manage research methods
- allow online editing
- activate specific functional modules
- define permissions to access services and to use functional modules at the individual user level



G3W-Suite - Editing on line Public buildings management3		A term
B modes	Alexan	×
B Mini		
Q. Starch	Tublic buildings (1)	1
() teadades	A NON NON	
O typeobleting	A P Destrue antiskowe.	
O her		
O transient	Sandida Sandida	
😫 fads	A Second Second Second	
THE REP.		
Layers tase taged		
Regist circle on individual layor to access a distance		
V Protectualities and second a	Constant and Const	
 ✓ Eterminationeterer Ø exec 		
28 Parchi puttolici		-
E faile taileig:	Fabbricati (2) 🛛 🖥	1
✓ Otele dileve □ Otele dileve	Coliz can lagte Happin	
		+
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	+

CHAPTER

ONE

RAW INSTALLATION

The following instructions are for a Ubuntu 22.04 LTS.

1.1 Install required packages

First step is install dev libraries packages for python module

```
sudo apt-get install -y \
    libxml2-dev \
    libxslt-dev \
    postgresql-server-dev-all \
    libgdal-dev \
    python3-dev
```

If you are running a ubuntu Server version is necessary to install also a XServer for the Qt libraries. Is possible install XVFB a virtual framebuffer X server for X Version 11 and run it.

```
sudo apt intall -y xvfb
sudo Xvfb :99 -screen 0 640x480x24 -nolisten tcp &
export DISPLAY=:99
```

I suggest you to create a systemd service to run it on bootstrap.

1.2 Install QGIS Server

```
wget -q0 - https://qgis.org/downloads/qgis-2022.gpg.key | sudo gpg --no-default-keyring_

--keyring gnupg-ring:/etc/apt/trusted.gpg.d/qgis-archive.gpg --import

sudo chmod a+r /etc/apt/trusted.gpg.d/qgis-archive.gpg

sudo bash -c "echo \"deb [arch=amd64] https://qgis.org/ubuntu-ltr jammy main\" >> /etc/

-apt/sources.list"

sudo apt update && sudo apt install -y python3-qgis qgis-server
```

1.3 Installation of node.js and Yarn

G3W-ADMIN use javacript package manager Yarn and Node.js

```
sudo curl -sS https://dl.yarnpkg.com/debian/pubkey.gpg | sudo apt-key add -
echo "deb https://dl.yarnpkg.com/debian/ stable main" | sudo tee /etc/apt/sources.list.d/
→yarn.list
sudo apt-get update && sudo apt install -y yarn
```

1.4 Create virtualenv

Install the follow python package Virtualenvwrapper

The following instructions are for python 3.10

Install python pip and virtualenvwrapper

sudo apt-get install python3-pip && sudo pip3 install virtualenvwrapper

Create a directory where to create environments for your virtualenvs.

mkdir <path_to_virtualenvs_directory>

To activate virtuenvwrapper on system login, add follow lines to 'bashrc' config file of your user

```
nano ~/.bashrc
....
export WORKON_HOME=<path_to_virtualenvs_directory>
export VIRTUALENVWRAPPER_PYTHON=/usr/bin/python3
source /usr/local/bin/virtualenvwrapper.sh
```

Login again with your user to activate Virtualenvwrapper

sudo su <my_ubuntu_username>

1.5 Virtualenv creation

To create a virtualnenv is sufficient call mkvirtualenv follow by the identification name for virtualenv (to use QGIS API into a virtualenv only solution is to give access python system site-packages to it using *–system-site-packages* option)

mkvirtualenv --system-site-packages g3wsuite

This last command just make active your new virtualenv environment, for the next times is possible use the follow command to activate the virtualenv environment:

workon g3wsuite

1.5.1 Use of native venv Python3

For G3W-SUITE deploy clearly can be used the native Python3 venv module, virtualenvwrapper is a third part module that render the use and management of virtual environments very simple.

1.6 Install G3W-SUITE

1.6.1 Clone code from github

```
git clone https://github.com/g3w-suite/g3w-admin.git
```

1.6.2 Set local_config.py file

. . .

G3W-ADMIN is a Django application, and to work is necessary set a config.py file. To start copy local_settings.example.py and set the databse and other:

```
cd g3w-admin/g3w-admin/base/settings
cp local_settings_example.py local_settings.py
```

set database, media root and session cookies name:

```
DATABASES = \{
    'default': {
        'ENGINE': 'django.contrib.gis.db.backends.postgis',
        'NAME': '<db_name>',
        'USER': '<db_user>',
        'PASSWORD': '<db_user_password>',
        'HOST': '<db_host>'.
        'PORT': '<db_port>',
    }
}
. . .
DATASOURCE_PATH = '<static_path_to_gis_data_source>'
. . .
MEDIA_ROOT = '<path_to_media_root>'
. . .
SESSION_COOKIE_NAME = '<unique_session_id>'
```

1.6.3 With paver commands

G3W-ADMIN has a series of paver CLI commands to administrate the suite. After prepared environment if sufficient invoke paver *install* task

paver install

1.6.4 Run G3W-SUITE

To run the application with paver

paver start

and for stop

paver stop

G3W-ADMIN is a django application so is possible run app by standard django manage.py commands

./manage.py runserver

1.7 Deploy G3W-SUITE

As other Django application, G3W-SUITE can be deployed by its wsgi capabilities. On the web if simple to find tutorial for deploy a Django application.

The simpler way is to use Apache2 as server WEB and its mod_wsgi module.

Alternative solutions are:

- Apache2 + mod_proxy + Uwsgi
- Apache2 + mod_proxy + Gunicorn
- Nginx + Uwsgi
- Nginx + Gunicorn

1.8 Manual installation steps

The preferred installation is by using the **paver** script as mentioned above, but in case you need to customize the installation process, here are the build and setup steps:

1.8.1 Build static js code

Make sure build components are available in static and collected later

```
cd g3w-admin/core/static
ln -s "../../node_modules/@bower_components" bower_components
```

1.8.2 Install requirements

Possibly within a virtual env:

```
pip install -r requirements.txt
pip install -r requirements_huey.txt
```

1.8.3 Django setup

```
python manage.py collectstatic --noinput
python manage.py migrate --noinput
```

Install some fixtures for EPSG and other suite options:

```
for FIXTURE in 'BaseLayer.json' 'G3WGeneralDataSuite.json' 'G3WMapControls.json'
G3WSpatialRefSys.json'; do
    python manage.py loaddata core/fixtures/${FIXTURE}
done
```

Sync menu tree items (re-run this command in case you installed optional modules and they are not visible in the admin menu tree):

python manage.py sitetree_resync_apps

1.9 Continuous integration testing

CI tests are automatically run on GitHub by custom actions.

The Docker compose configuration used in the CI tests is available at docker-compose.latest.yml.

The testing image is built from the dependency image and it will run all install and build steps from the local repository.

The dependency image is built from the Dockerfile.deps.

G3W-SUITE supports the latest LTR QGIS version, so at now is the 3.22, therefore there are also dockerfiles and docker compose files for this version:

- docker-composer.322.yml
- Dockerfile.32..deps

CHAPTER

TWO

DOCKERIZATION

This repository contains scripts and recipes for deploy of the G3W-SUITE web-gis application with Docker and Docker compose .

2.1 Deploy

Follow steps to deploy G3W-SUITE on a Ubuntu Server (20.04)

2.1.1 Configuration

Create a file .env (or copy .env.example and rename it in .env) and place it in the main directory, the file will contain the database credentials (change <your password>) and other settings:

```
# External hostname, for docker internal network aliases
WEBGIS_PUBLIC_HOSTNAME=demo.g3wsuite.it/
# This volume is persistent and mounted by all
# containers as /shared-volume
WEBGIS_DOCKER_SHARED_VOLUME=/tmp/shared-volume-g3w-suite
# DB setup
G3WSUITE_POSTGRES_USER_LOCAL=g3wsuite
G3WSUITE_POSTGRES_PASS=<your_password>
G3WSUITE_POSTGRES_DBNAME=g3wsuite
G3WSUITE_POSTGRES_HOST=postgis
G3WSUITE_POSTGRES_PORT=5432
```

Description of other environment variables that can be used, are available on Docker environment variables

2.1.2 Run

docker-compose up -d

If all went well, G3W-SUITE run on http://localhost:8080

g3w-admin	○ □ ≈ ⊗ localhost	8080/en/login/?next=/en/		☆	⊘ ۶	Ø	€ €	■
		g3w su	ITE					
		Sign in to start your ses	sion					
		Username	1					
		Password	a					
		Sign In						
		Version 3.4.dev-202203231	31824					

2.2 G3W-SUITE with consumer image

G3W-SUITE use huey for bach processing (https://github.com/coleifer/huey), so if you want to use it, use docker-compose-consumer.yml file on deploy:

docker-compose -f docker-compose-consumer.yml up -d

2.3 Builds

Docker compose will download images from docker hub (https://hub.docker.com/u/g3wsuite), but is also possible build main image of G3W-SUITE and other docker-compose images.

2.3.1 G3W-SUITE

The main suite docker image can be built with:

```
docker build -f Dockerfile.g3wsuite.dockerfile -t g3wsuite/g3w-suite:dev --no-cache .
```

The image is build from https://github.com/g3w-suite/g3w-admin.git --branch dev and from a dependencies base image Dockerfile.g3wsuite-deps.ltr.dockerfile, the dependencies image can be built with:

Usually is sufficient make build of main docker image g3wsuite/g3w-suite:dev, the build of dependence image g3wsuite/g3w-suite-deps-ltr:dev is done to update last QGIS LTR version.

2.3.2 Postgis

Postgis image can be built with:

```
docker build -f Dockerfile.postgis.dockerfile -t g3wsuite/postgis:11.0-2.5 .
```

The Docker hub name for this image is g3wsuite/postgis:11.0-2.5

2.4 Setups

2.4.1 PG_SERVICE

To use of PostgreSql Service, put your service setups into ./scripts/pg_service.conf file, the conf file will be mounted into docker container at runtime to PGSERVICEFILE path position.

2.4.2 HTTPS additional setup

To active https with LetsEncrypt just follow the following instructions:

- move config/_nginx/django_ssl.conf to config/nginx/django_ssl.conf
- check the domain name in the .env file and in config/nginx/django_ssl.conf
- run: docker pull certbot/certbot
- launch ./run_certbot.sh
- activate 301 redirect into config/nginx/django.conf
- restart compose
- make sure the certs are renewed by adding a cron job with crontab -e and add the following line: 0 3 * * * /<path_to_your_docker_files>/run_certbot.sh

• if you disabled HTTPS, you can move config/nginx/django_ssl.conf back to its original location now, and restart the Docker compose to finally enable HTTPS

2.4.3 Volumes

Data, projects, uploads and the database are stored in a shared mounted volume shared-volume, the volume should be on a persistent storage device and a backup policy must be enforced.

Currently, the volume is mounted in /tmp/shared-volume-g3wsuite-dev. In production environments it is encouraged to change this to a permanent location. This can be done by modifying the .env file.

2.4.4 First time setup

- log into the application web administation panel using default credentials (admin/admin)
- change the password for the admin user and for any other example user that may be present

2.4.5 Caching

Tile cache can be configured and cleared per-layer through the webgis admin panel and lasts forever until it is disabled or cleared.

Tip: enable cache on linestring and polygon layers.

2.4.6 Editing

Editing module is active by default, to avoid simultaneous feature editing by two or more users, the editing module works with a feature lock system. This locking system can remain active if users do not exit the editing state correctly, to avoid this it is advisable to activate a cron job on host machine that checks the features that have been locked for more than 4 hours and frees them:

```
0 */1 * * * docker exec -e DISPLAY=:99 g3w-suite-docker_g3w-suite_1 python3 /code/g3w-

→admin/manage.py check_features_locked
```

2.5 Front-end App

Set the environment variable

FRONTEND=**True**

This will set the front end app as the default app

2.6 Style customization

Templates can now be overridden by placing the overrides in the config/g3w-suite/overrides/templates, a Docker service restart is required to make the changes effective.

The logo is also overridden (through config/g3w-suite/settings_docker.py which is mounted as a volume), changes to the settings file require the Docker service to be restarted.

A custom CSS is added to the pages, the file is located in config/g3w-suite/overrides/static/style.css and can be modified directly, changes are effective immediately.

2.7 Performances optimization

General rules (in no particular order: they are all mandatory):

- 1. set scale-dependent visibility for the entire layer or for some filtered features (example: show only major roads until at scale 1:1E+6)
- when using rule-based/categorized classification or scale-dependent visibility create indexes on the column(s) involved in the rule expression (example: "create index idx_elec_penwell_ious on elec_penwell_ious (owner);"
- 3. start the project with only a few layers turned on by default
- 4. do not turn on by default base-layers XYZ such as (Google base maps)
- 5. do not use rule-based/categorized rendering on layers with too many categories (example: elec_penwell_public_power), they are unreadable anyway
- 6. enable redering simplification for not-point layers, set it to Distance 1.2 and check Enable provider simplification if available

2.8 PostgreSQL administration

Postgres is running into a Docker container, in order to access the container, you can follow the instruction below:

2.8.1 Check the container name

```
$ docker ps | grep postgis
84ef6a8d23e6 g3wsuite/postgis:11.0-2.5 "/bin/sh -c /docker-..." 2 days_
→ago Up 2 days 0.0.0.0:5438->5432/tcp g3wsuitedocker_
→postgis_1
```

In the above example the container name is g3wsuitedocker_postgis_1

2.8.2 Log into the container

\$ docker exec -it g3wsuitedocker_postgis_1 bash

2.8.3 Become postgres user

root@84ef6a8d23e6:/# su - postgres

2.8.4 Connect to postgis

```
postgres@84ef6a8d23e6:~$ psql
psql (11.2 (Debian 11.2-1.pgdg90+1))
Type "help" for help.
```

postgres=#

2.9 Portainer usage

Portainer (https://www.portainer.io) is a docker-based web application used to edit and manage Docker applications in a simple and intuitive way.

Plese refer to the Add new stack section to learn how to deploy the docker-compose-consumer.yml stack with Portainer (>= v2.1.1).

2.9.1 Contributors

- Walter Lorenzetti Gis3W (@wlorenzetti)
- Alessandro Pasotti ItOpen (@elpaso)
- Mazano Kartoza (@NyakudyaA)
- Matteo Tosi Gis3w (@Raruto)

CHAPTER

THREE

DOCKER ENVIRONMENT VARIABLES

The following environment variables used to deploy G3W-SUITE by docker (https://github.com/g3w-suite/g3w-suite-docker).

They must added to .env deploy file.

3.1 Requirements variables

3.1.1 WEBGIS_PUBLIC_HOSTNAME

The domain to which the application will respond.

3.1.2 WEBGIS_DOCKER_SHARED_VOLUME

The path on which the docker permanent volume will be mounted with the application data inside.

Database connections parameters

The follow variables re for set the connection to G3W-SUITE administration database.

3.1.3 G3WSUITE_POSTGRES_USER_LOCAL

Database username to connect to G3W-SUITE database. If you are going to use docker postgis image, it'll be created on first run of container.

3.1.4 G3WSUITE_POSTGRES_PASS

Database username password to connect to G3W-SUITE database. If you are going to use docker postgis image, it'll be created on first run of container.

3.1.5 G3WSUITE_POSTGRES_DBNAME

Database name of G3W-SUITE database connect to. If you are going to use docker postgis image, it'll be created on first run of container.

3.1.6 G3WSUITE_POSTGRES_HOST

Database host value connect to. If you are going to use docker postgis image, it'll be set to postgis

3.1.7 G3WSUITE_POSTGRES_PORT

Database port value connect to. If you are going to use docker postgis image, it'll be set to 5432

3.2 Other not required settings

3.2.1 TILESTACHE_CACHE_TOKEN

A custom unique token to use for internal caching request. Default value is : 374h5g96831hsgetvmkdel.

3.2.2 TILESTACHE_CACHE_BUFFER_SIZE

Tile width/height tile map dimension. Default value is: 256.

3.2.3 G3WSUITE_TILECACHE_PATH

Internal path to folder to save tiles of map. Dafault value is: /shared-volume/tile_cache/.

Gunicorn settings

G3W-SUITE with docker is deployed with Gunicorn.

3.2.4 G3WSUITE_GUNICORN_NUM_WORKERS

Number of workers Gunicorn has to start with. Default: 8. Usually then number of workers is equal to number of processor x 2.

3.2.5 G3WSUITE_GUNICORN_MAX_REQUESTS

Number of requests after that gunicorn worker restart. Default: 200. Thi is used to compensate the python/gunicorn memory leaks.

QGIS server variables

Every QGIS environment variables available as specified on manual https://docs.qgis.org/3.22/en/docs/server_manual/ config.html#environment-variables can be set, important is remember to add thy to *docker-compose.yml* o *docker-compose.yml*.

The following varaible are just set into docker-compose files:

3.2.6 PGSERVICEFILE

Put your pg services into *./scripts/pg_service.conf file*, the conf file will be mounted into docker container at runtime to PGSERVICEFILE path position.

3.2.7 QGIS_SERVER_LOG_FILE

3.2.8 QGIS_SERVER_LOG_LEVEL

Openrouteservice

3.2.9 ORS_API_ENDPOINT

Openrouteservice API end point. Default: 'https://api.openrouteservice.org/v2'.

3.2.10 ORS_API_KEY

Openrouteservice API key Optional, can be blank if the key is not required by the endpoint

3.2.11 ORS_MAX_RANGES

Max number of ranges (it depends on the server configuration) Default: 6.

3.2.12 ORS_MAX_LOCATIONS

Max number of locations(it depends on the server configuration) Default: 2.

Frontend module

3.2.13 FRONTEND

If true install and activate G3W-SUITEfrontend module https://github.com/g3w-suite/g3w-admin-frontend

CHAPTER

FOUR

SETTINGS

The following variables can be added to or edited in the project's local_settings.py:

4.1 Base settings

4.1.1 G3WADMIN_PROJECT_APPS

Custom django map server module other than qdjango (QGIS-Server provider)

4.1.2 G3WADMIN_LOCAL_MORE_APPS

Custom django modules that is possible to add, i.e. g3w-admin-frontend (https://github.com/g3w-suite/g3w-admin-frontend) module and other third part django modules. G3W-SUITE accessory modules:

- g3w-admin-frontend (https://github.com/g3w-suite/g3w-admin-frontend)
- caching
- filemanager
- editing

4.1.3 DATASOURCE_PATH

Path to geo data directory (shp, Spatialite, raster, etc..).

4.1.4 G3WFILE_FORM_UPLOAD_FORMATS

List of formats file that *file form ajax uploader* can manage at global level. Default is ['qgs', 'qgz', 'png', 'jpg', 'jpg', 'pdf', 'doc', 'docx', 'xls', 'xlsx', 'ods']

Important: Last part of path could be common with QGIS project datasource path. I.e.:

QGIS project: <datasource>/<path>/<to>/project_data/<geodata>.shp</datasource>

local_settings.py: DATASOURCE_PATH = /<local_server_<path>/<to>/**project_data**

Mandatory.

4.1.5 G3WADMIN_VECTOR_LAYER_DOWNLOAD_FORMATS

Default is ['shp', 'xls'], set download data format. Values possible:

- *shp*: download into Esri Shape format.
- *xls*: download into Excel format
- gpx: download into GPS format (only for Point and Line layers)

4.1.6 RESET_USER_PASSWORD

Default is *False*, set tot *True* to activate reset user password by email workflow. If set to True remember to set Django emailing settings (https://docs.djangoproject.com/en/2.2/topics/email/).

4.1.7 CLIENT_OWS_METHOD

Default is 'GET', set to 'POST' to change default http call method.

4.2 Database logging

With v3.6.x version G3W-SUITE can save message logs inside the database. To activate it is sufficient add a new log *handler* inside Django *LOGGING* settings and use it for a *logger*:

```
LOGGING = {
    'handlers': {
         . . .
         'db_log': {
             'level': 'DEBUG',
             'class': 'core.utils.logs.db_handler.DatabaseLogHandler'
             },
         . . .
    }
    . . .
    'loggers': {
         . . .
         '': {
              'handlers': ['db_log'],
             'level': 'DEBUG',
         },
         . . .
    }
}
```

Important: This logging system continues to save log records with no upper limit. To keep the table from getting too big, there is a *django command* that deletes records older than a set number of days. Is possible set a cronjob with the follow command:

python3 manage.py clear_db_logs -days 30

In this case records older than 30 days will be deleted.

4.3 Frontend portal setting

4.3.1 FRONTEND

Default is False, set to True for activate **G3W-SUITE** frontend portal like g3w-admin-frontend. If it's set to True base url path for G3W-SUITE admin section become */admin/*.

4.3.2 FRONTEND_APP

Module name added to G3WADMIN_LOCAL_MORE_APPS to use as portal-frontend. I.e.:

4.4 General layout settings

4.4.1 G3WSUITE_POWERD_BY

Default is True, set to False for don't show bottom attribution informations.

4.4.2 G3WSUITE_CUSTOM_STATIC_URL

A custom url from to load custom static files as images, css, etc..

4.4.3 G3WSUITE_MAIN_LOGO

Main admin section logo image. Mandatory is set G3WSUITE_CUSTOM_STATIC_URL

4.4.4 G3WSUITE_RID_LOGO

Main admin section reduced logo image. Mandatory is set G3WSUITE_CUSTOM_STATIC_URL

4.4.5 G3WSUITE_LOGIN_LOGO

Login logo image. Mandatory is set G3WSUITE_CUSTOM_STATIC_URL

4.4.6 G3WSUITE_CUSTOM_TITLE

G3W-SUITE html page title. If is not set, title is: g3w-admin for admin section and g3w-client for webgis client.

4.4.7 G3WSUITE_FAVICON

Favorite icon image. Mandatory is set G3WSUITE_CUSTOM_STATIC_URL

4.4.8 G3WSUITE_CUSTOM_CSS

A list of custom css files added to *admin* pages and to the *client*. Mandatory is set G3WSUITE_CUSTOM_STATIC_URL. I.e.:

```
G3WSUITE_CUSTOM_CSS = [
   G3WSUITE_CUSTOM_STATIC_URL +'css/custom.css'
]
```

4.4.9 G3WSUITE_CUSTOM_JS

A list of custom js files added to *admin* pages and to the *client*. Mandatory is set G3WSUITE_CUSTOM_STATIC_URL. I.e.:

```
G3WSUITE_CUSTOM_JS = [
G3WSUITE_CUSTOM_STATIC_URL +'js/custom.js'
]
```

4.5 Client layout settings

4.5.1 G3W_CLIENT_SEARCH_TITLE

Custom webgis client search section title.

4.5.2 G3W_CLIENT_SEARCH_ENDPOINT

Search url endpoint for 'searches calling', default ows.

- ows: by wms search;
- *api*: by g3w-suite layer vector API.

4.5.3 G3W_CLIENT_HEADER_CUSTOM_LINKS

A list of dict of custom links to add into main top bar of webgis client. I.e.:

```
G3W_CLIENT_HEADER_CUSTOM_LINKS = [
     {
         'url': 'https://gis3w.it',
         'title': 'Gis3W company',
         'i18n': True, #(False as default value)
         'target': '_blank'
         'img': 'https://gis3w.it/wp-content/uploads/2016/10/logo_qgis-1-100x100.png?
→x22227'
     },
     {
        'title': 'Modal 1',
        'content': 'Html example content to show in modal',
        'type': 'modal',
        'position': 10
   },
]
```

i18n (optional) set True if you want lent client try to translate title.

4.5.4 G3W_CLIENT_LEGEND

A dict to customize QGIS-server legend image generate with WMS GetLegendGraphics request. I.e.:

```
G3W_CLIENT_LEGEND = {
    'color': 'red',
    'fontsize': 8,
    'transparent': True,
    'boxspace': 4,
    'layerspace': 4,
    'layertitle': True,
    'layertitlespace': 4,
    'symbolspace': None,
    'iconlabelspace': 2,
    'symbolwidth': 8,
    'symbolheight': 4
}
```

4.5.5 G3W_CLIENT_RIGHT_PANEL

Custom properties settings for webgis right panel section (default, width 33%). A the moment only *width* is managed. I.e.:

```
G3W_CLIENT_RIGHT_PANEL = {
    'width': 33
}
```

4.5.6 G3W_CLIENT_NOT_SHOW_EMPTY_VECTORLAYER

Default is False. Set to True for remove from webgis TOC vector layer empty, without data.

4.5.7 GEOCONDING_PROVIDERS

Set the geocoding providers available for webgis services:

```
GEOCODING_PROVIDERS = {
    "nominatim": {
        "label": "Nominatim (OSM)",
        "url": "https://nominatim.openstreetmap.org/search"
    },
}
```

You can also add custom providers (or edit the existing ones within *static/client/geocoding-providers* folder), just remember to use javascript file name as "provider" identifier:

```
https://dev.g3wsuite.it/static/client/geocoding-providers/nominatim.js
https://dev.g3wsuite.it/static/client/geocoding-providers/bing_streets.js
https://dev.g3wsuite.it/static/client/geocoding-providers/bing_places.js
https://dev.g3wsuite.it/static/client/geocoding-providers/your_custom_provider.js
```

```
VENDOR_KEYS['bing'] = 'bing.secret.key'
GEOCODING_PROVIDERS = {
"nominatim": {
   "label": "Nominatim (OSM)",
   "url": "https://nominatim.openstreetmap.org/search",
   # "icon": "road",
},
 "bing_streets": {
    "label": "Bing Streets",
    "url": "https://dev.virtualearth.net/REST/v1/Locations/?key=" + VENDOR_KEYS['bing'],
    # "icon": "road",
 },
 "bing_places": {
    "label": "Bing Places",
    "url": "https://dev.virtualearth.net/REST/v1/LocalSearch/?key=" + VENDOR_KEYS['bing
\leftrightarrow '],
    # "icon": "poi",
  },
```

(continues on next page)

(continued from previous page)

```
"your_custom_provider": {
    "label": "Custom Provider",
    "url": "url": "https://your-custom-server.com/Search/?key=super.secret.key",
    "icon": "poi",
    },
}
```

NB: for more info see: *Getting a Bing maps key <https://learn.microsoft.com/en-us/bingmaps/getting-started/bing-maps-dev-center-help/getting-a-bing-maps-key>*

4.6 Editing settings

Settings params for editing module.

4.6.1 EDITING_SHOW_ACTIVE_BUTTON

Default is True. Set to False for not show editing button activate/deactivate into layers project list.

4.6.2 EDITING_ANONYMOUS

Default is False. Set to True to render possible give to anonymous user editing permissions.

4.6.3 EDITING_LOGGING

Default is False. Set to True to log users editing action into database.

4.7 Caching settings

Settings params for caching module

4.7.1 TILESTACHE_CACHE_NAME

A name to identify caching

4.7.2 TILESTACHE_CACHE_TYPE

Default is Disk to save tile on a disk. Set to Memcache for to use *Memcached* caching framework (https://www.memcached.org/)

4.7.3 TILESTACHE_CACHE_DISK_PATH

Path to disk space where to save tile created by tilestache if TILESTAHCE_CACHE_TYEPE is se to Disk.

4.7.4 TILESTACHE_CACHE_TOKEN

Mandatory, strign to use as token for internal WMS call for caching module.

4.8 Filemanger settings

Settings params for filemanager module.

4.8.1 FILEMANAGER_ROOT_PATH

Mandatory, path to disk space where to CRUD geo data files i.e. Shp Raster, etc.

4.8.2 FILEMANAGER_MAX_UPLOAD_N_FILES

Default is 5, max number files to upload simultaneously.

4.9 **Qplotly settings**

4.9.1 LOAD_QPLOTLY_FROM_PROJECT

Default is False, set to True to import DataPlotly settings from QGIS project.

4.10 Openrouteservice settings

4.10.1 ORS_API_ENDPOINT

Default is http://localhost:8080/ors/v2/, this is the endpoint for Openrouteservice API.

4.10.2 ORS_API_KEY

Openrouteservice API key, optional, can be blank if the key is not required by the endpoint.

4.10.3 ORS_PROFILES

List of available Openrouteservice profiles, default: ("driving-car", "driving-hgv")

4.11 Vendors settings

Settings variables about third part services, i.e. Google API etc..

4.11.1 VENDOR_KEYS

A list with services API keys. I.e.:

```
VENDOR_KEYS = {
  'google': 'fhgnrjwipòflsjhjjdhjdhashhabs',
  'bing': 'agbsgtrkADgstejaaklkklkds8irncdfk'
}
```

At the moment only *Google* and *Bing* services are supported, for background base map and for google geoconding service plus of *Nominatim* default service.

4.12 Google reCAPTCHA

Google reCAPTCHA system can be added to *login form* and to *password reset form* ((is activated)) and *registration form* (is activated)

4.12.1 RECAPTCHA

Default is False, active or deactive Google reCAPTCHA checkbox.

4.12.2 RECAPTCHA_VERSION

Default is 2, reCAPTCHA version 2 or 3

4.12.3 RECAPTCHA_PUBLIC_KEY

Required if RECAPTCHA is True, Google reCAPATCHA public key.

4.12.4 RECAPTCHA_PRIVATE_KEY

Required if RECAPTCHA is True, Google reCAPATCHA private key.

4.13 Registration

Settings variables for user registration system.

4.13.1 REGISTRATION_OPEN

Default is False, Activate/deactivate the user registration system.

4.13.2 REGISTRATION_ACTIVE_BY_ADMIN

Default is False, if True the activation of a self-signed user must be done by administrator user.

4.13.3 ACCOUNT_ACTIVATION_DAYS

Default is 2, this is the number of days users will have to activate their accounts after registering. If a user does not activate within that period, the account will remain permanently inactive unless a site administrator manually activates it.

4.13.4 REGISTRATION_EMAIL_SUBJECT_PREFIX

Default [G3W-SUITE], Prefix for email subjects of Registration workflow: activation, activated and activation admin email.

4.13.5 REGISTRATION_EMAIL_BODY_SIGN

Default g3wsuite.it, Email's sign of emails of Registration workflow: activation, activated and activation admin email.

4.14 Caching

Settings variables for *caching* workflow

CHAPTER

INTRODUCTION

G3W-SUITE is a modular client-server application for the management and publication of interactive map projects.

The framework was born from the need to have a software capable of **publishing**, in total autonomy and in a simple and fast way on a webgis client, cartographic projects realized with QGIS.

The following aspects will be analyzed within the manual:

- · organization and optimization of data and QGIS projects for web publishing
- organization of cartographic contents in a hierarchical way: macro groups and cartographic groups
- · user management and access control systems for consultation and management of webgis services
- · management of the online editing function for the creation of web cartographic management systems
- · publishing and managing QGIS projects as WebGis services
- creation of searches, visualization of graphics created with the DataPlotly plugin and definition of constraints (geographic and alphanumeric) on visualization and editing permissions

The current release (3.7) is compatible with QGIS 3.28.x LTR (Server and Desktop).

🗋 📛 🖶 🖶 🔀 😫 💕	u 🖬 🗛 👧 🍳 👯 🍳 🗨 🏶 🛄	5 🕛 🌫 🔍 🔍 - 🔣 - 💊 - 🌄 🗰	Σ 🛲 • 🤛 💷 •		
i 🦪 省 VG 🔏 🖷 i 🖉 🖊	* 🖶 🕾 旅 - 運 亩 🛰 🖻 🖶 🛷 ! 🛥	🍕 📆 🧠 🤫 🤫 🧠 🗐 😫 👌 🧷 🛛	2		
arowser Favorites Favorites Favorites Folget Home Folget Home			A4 Wings 952 952 952 952 952 952 952 952 952 952	22 5 5 60 60 60 60 60 60 60 60 60 60 60 60 60	
Layers (A) R, (A) R, (88 sta	Area 1			92 92 551 551 549 553
Maintenance work	Identification		Documents		ma
 ✓ ④ Bac map ✓ Ø S[*] CTR multiscale 	Id Name Address Type Vear of construction	10 Caribaldi Palace Via Alfredo Orlani gla' Via Vecchia Residential 2020	Photo edificistrani-mei-mon Data sheet Evaluation-Form Mbr Link https://gswsuite.it Categoria	to-crooked-house-polonia-768x3c nbtsty.pdf Cancel OK	
○ Type to locate (Ctrl+K)	No features at this position found.	Coordinate 12	52104.7,5433417.9 🕷 Scale 1:1895 💌 🚔 M	agnifier 100% 🗘 Rotation 0,0	• 🗘 🛛 Render 💮 EPSG:3857 🔍



5.1 Version

At the moment it's not used a classic versioning system for the suite, this branches are avialable.

5.2 Main contributors

- Walter Lorenzetti Gis3W (@wlorenzetti)
- Leonardo Lami Gis3W (@leolami)
- Francesco Boccacci Gis3W (@volterra79)
- Alessandro Pasotti QCooperative (@elpaso)
- Luigi Pirelli QCooperative (@luipir)
- Mazano Kartoza (@NyakudyaA) (Dockerization refactoring)
- Tudor Barascu Kartoza (@tudorbarascu)
TECHNOLOGICAL INFRASTRUCTURE

The publishing system is based on a series of OS tools and software

- PostgreSQL/PostGis: for the management of application data
- PostgreSQL/PostGis or SpatiaLite: for the management of geographic data
- **QGIS Server LTR** as OGC services server
- G3W-ADMIN the Administration component: developed in Python using Django
- G3W-CLIENT the Cartographic client: based on OpenLayers3 and developed with reactive tecnology by Vue.js
- The main libraries used for the management and the visualization of the geographical part and the interaction with the user are: **OpenLayer, Boostrap, jQuery, Lodash and Vue.js**.
- Gulp.js as task runner





Below is a diagram relating to the standard workflow

SEVEN

MANAGEMENT AND ORGANIZATION OF GEOGRAPHIC DATA AND QGIS PROJECTS

This section describes how to organize QGIS data and projects locally and how to synchronize them on the server environment for publication purposes

Thanks to the integration with the APIs of QGIS it is now possible to manage the main formats (geographic or not) supported by QGIS Server:

- reading and editing mode
 - PostGreSQL/PostGIS
 - Oracle Spatial (compiling QGIS Server)
 - SQLite/SpatiaLite
 - GeoPackage
 - ShapeFile
- reading mode
 - SQL Server
 - Virtual layer

The suite also allows you to manage the consultation and editing of:

- simple join data with no nesting limits
- 1:N relation data
- N:M relation data

7.1 Data on DB Server

If your geographic data is stored on Server DB, it will be sufficient to allow access to the DB from the IP address on which the application is installed.

7.2 Data on SpatiaLite/GeoPackage or OGR format

If your geographical data are stored on SpatiaLite, GeoPackage or an other physical files (.shp, .kml, .tif...) located on your local PC, you will need:

- organize data and projects in predefined local directories and subdirectories
- **upload/synchronize geographic data to the corresponding folder located on the server** where the application is installed

Of course, mixed solutions with geographical data on PostGreSQL/PostGIS, SpatiaLite and other formats will also be possible.

7.2.1 Organization of data and projects

Data on physical files and / or on GeoDB SpatiaLite and QGIS cartographic projects must be organized in compliance with the following indications:

- a main directory named and positioned in according to need's user
 - a **project_data sub-directory** that must contain the **geographic data** used for the various cartographic projects, such data can also be organized in subdirectories with no nesting limits.
 - a projects sub-directory that must contain the QGIS cartographic projects (.qgz or .qgs files)



NB: The name of the local directory dedicated to geographic data must correspond to the name defined for the **DATASOURCE_PATH** variable set during installation. See dedicated paragraph.

That directory is also used to contain **images used in the print layouts** associated with the QGIS cartographic projects.

7.2.2 Geographical data synchronization on the server

The data stored in the local **project_data** directory must be synchronized on the server where the G3W-SUITE application is installed.

The geographic data stored in the local **project_data** folder must be loaded, reflecting any subdirectory structure.

To synchronize your data access to the Administration panel of G3W-ADMIN and click on the Configurations icon



located in the upper right corner.

Choose the File Manager item in the linked menu.





Using this tool it is possible to manage the physical geographic data on the server in a simple and intuitive way.

The root directory of the File Manager corresponds to the local project_data directory

It will therefore be necessary, in the case of using geographic files on the file system, to synchronize the contents of the local **project_data** directory (and any sub-directories) before proceeding with the publication of QGIS projects.

Two specific directories can also be created within the root directory of the File Manager:

- media_user: a directory exposed on the web, to store your multimedia files
- svg: a directory to store extra SVG icons used your QGIS projects

All the directories can be organized in subdirectories with no nesting limits.

NB: The names of these directories are defined by the basic settings set during the installation of the suite. See dedicated paragraph.

GOWSUITE Current folde	n 🍵 🖵 🌪 🗂 🔠		∞ @ ≫ ங ங =	L Upload 🍃 New folder 🛛 🚽
휴 media_user 호 🗃 svg	geopackage	spatialite	media_user	svg

The example shows the case in which in the local **project_data** directory there are two directories (**geopackage** and **spatialite**) in addition to the two system directories (**svg** and **media_user**).

7.2.3 Accessed the File Manager tool

Which users can access and manage data on FileManager?

- Admin role users
- Editor1 role users

In the next chapter the powers and limits of the two roles will be described in detail.

EIGHT

HIERARCHICAL ORGANIZATION OF WEBGIS SERVICES AND TYPES OF USERS (ROLES)

This paragraph allows you to understand how G3W-SUITE makes it possible to manage the individual WebGis services in a structured and hierarchical way.

In G3W-SUITE it is possible to organize WebGis services on two thematic/functional levels

- Cartographic MacroGroups
 - Cartographic groups

These organizational levels can be associated with different types of users (Editor 1, Editor2 and Viewer) in order to manage the access/management powers to the individual elements in a granular way.

The following image shows an example of the functional use of these organizational levels within a Union of Municipalities.

Access policies and individual functional modules may be associated with each WebGis service.



8.1 Types of Users (Roles)

In G3W-SUITE you can create Users and Users Groups and associate them with specific roles:

- Admin1: user with full powers including Django administration (basic suite configuration)
- Admin2: user with full powers excluding those of Django administration (basic configuration of the suite)
- Editor1: administrator of one or more Cartographic MacroGroups for which it will be possible:
 - create users and/or user groups
 - create Cartographic Groups and, if necessary, assign them to an Editor 2 user
 - publish WebGis services and define their access policy
 - activate and configure some functional modules
- Editor2: administrator of one or more Cartographic Groups for which it will be possible:
 - publish/update WebGis services and define their access policy
 - activate and configure some functional modules
- Viewer: user with access permission in consultation on WebGis services characterized by authentication. This user can also use individual functional Modules if the relative permissions have been attributed to him
- Anonymus User: user to be associated with WebGis services and/or functional modules with free access

8.2 Hierarchical organization of contents

The following paragraph is dedicated to better understanding the relationships between the different types of users and the different elements of the suite (MacroGroups, Map Groups, WebGis services ...).

In G3W-SUITE it is possible to manage Webgis services in a more or less structured way

- an organizational level (Cartographic Groups):
- two organizational levels (MacroGroups and Cartographic Groups)

These hierarchical levels can be used for **organizational purposes** (thematic containers) and/or **functional** (containers managed by different users/roles).

It is in fact possible to associate the two types of containers (MacroGroups and Cartographic Groups) to users with different roles/powers (Editor1 and Editor2) who will thus become the Administrators of all their contents.

In particular Editor1 users will also be able to create/manage users who can be associated with the Cartographic Groups and WebGis services present in the reference MacroGroup.

The cases relating to one or two organizational levels will be better described below.

8.2.1 One organization level (absence of MacroGroups)

If MacroGroups are not needed, the Admin user will be the only administrator of the suite and can therefore:

- · create users (individuals and/or groups) of various types
- create Cartographic Groups
- publish WebGis services within the individual Cartographic Groups
- activate some specific modules on individual WebGis services

When creating a cartographic group, the Admin user can define:

- the eventual user (individual/group) Editor 2 to associate the Group with
- Viewers users (individuals/groups) who will have access to this container



In the event that the Cartographic Group is assigned to **Editor 2** (single or group users), they will may autonomously publish/update WebGis services inside in this container.

Editor 2 users will also be able to define the access policies to the published WebGis services, limited to the Viewers users associated with the Cartographic Group by the Admin user.

Even the **Admin** user can publish **WebGis services** within a Cartographic Group and, if necessary, associate them with a user (single and/or group) of **Editor 2** type.

8.2.2 Two organization levels (presence of MacroGroups)

Macrogroups can be created only by Admin users.

Each Macrogroup can be associated with only one Editor1 user.

Each MacroGroup can be considered as a watertight compartment within which the associated Editor 1 user (administrator of the MacroGroup), will be able to create users and user groups that will be made available to define access permissions for content (Groups Maps, WebGis services, functional modules ...) of the reference MacroGroup only.

In this way it will be possible to create totally independent entities, the MacroGroups, which will be managed exclusively by the user Editor 1 associated with them.

Clearly the Admin users (1 and 2) will continue to have full powers on all groups present in the system.



As previously specified, Editor 1 user will be able to:

- create users (single and/or groups) of type Editor2 and Viewer
- create Cartographic Groups within its Macro Group
- publish WebGis services within his Cartographic Groups
- activate specific modules on individual WebGis services

When Editor 1 user creates a Cartographic Group, he can define:

- the eventual Editor2 user (individual/group) to associate with this Group
- Viewers users (individuals/groups) who will have access to this container

8.3 Accessed the File Manager tool

As described in the previous chapter, the users who can access the FileManager are the following:

- Admin role users
- Editor1 role users

Admin role users will be able to access/edit/upload all the contents of the FileManager.

Editor1 role users (administrators of a specific MacroGroup) will be able to access/modify/upload only the contents present within a folder identified with the same user name as Editor1 itself.

Again from the perspective of an infrastructure dedicated to a Union of Municipalities, this will allow each Editor1 (manager of one Administrations) to be able to independently manage the geographical data of their own Administration.

8.4 Summary table of access/administration policies

Role	Description	Users	Cartographic MacroGroups	Cartographic Grups	WebGis Services	Editing
Admin1	Advanced administrator with possibility to act on the Django Administration component	Manages Editor1, Editor2 and Viewer users	Create and manage Cartographic MacroGroups and associate them with user Editor1	Create and manage Cartographic Groups Manages access/management permissions on the Group	Publish/manage WebGis services Manages access/management permissions on the service	It acts on all the layers on which the editing function is activated
Admin2	Basic administrator	Manages Editor1, Editor2 and Viewer users	Create and manage Cartographic MacroGroups and associate them with Editor1	Create and manage Cartographic Groups Manages access/management permissions on the Group	Publish/manage WebGis services Manages access/management permissions on the service	It acts on all the layers on which the editing function is activated
Editor1	Advanced manager user	Manages Editor2 and Viewer users Users created by an Editor1 user cannot be managed by other Editor1 users	Manages contents of the Cartographic MacroGroup assigned to him	Creates and manages Cartographic Groups within the Cartographic MacroGroup assigned to him Manages access/management permissions on the Group limited to users created by him	Publishes/manages WebGis services within the Cartographic Groups assigned to him Manages access/management permissions on the service limited to users created by him	It acts on the layers on which the editing function is activated, if contained in the Cartographic MacroGroup assigned to him
Editor2	Simple user manager	-	-	Manages Cartographic Groups assigned to him	Publishes/manages WebGis services within Cartographic Groups assigned to him	It works on the layers on which the editing function is activated, if contained in the Cartographic Groups assigned to him
Viewer	Viewer user	-	View Cartographic MacroGroups on the front end based on associated credentials	View Cartographic Groups on the front end based on the associated credentials	View WebGis services based on associated credentials	It acts on all the layers on which the editing function is activated, based on the associated credentials

Below is a summary table of the powers associated with the different roles.

QGIS: PROJECT SETTINGS

This section describes how to optimize your QGIS projects to publish as a WebGis service.

Thanks to the integration with QGIS Server, all the symbology aspects associated with the singoly layers are automatically reproduced on the WebGis service

In the QGIS cartographic projects you can set some parameters and options that affect functionalities and contents in the derivative WebGis service, such as:

- the webgis service identification name
- the associated **basic metadata**
- the capabilities of the service
- the possibility to exclude some associated print layouts on the WebGis service
- which layers are queryable and searchable
- which layers to expose with the different OGC services (WMTS, WFS, WCS)
- which fields (for each vector data) are exposed as WMS and/or WFS
- the Themes (Views) defined at the project level
- layer/group management from embedded projects
- the structure of the query form visible on the WebGis service
- the **editing widget**, **constraints** and **default values** (also based on QGIS expressions) for every fields of vector layers
- the associated print layouts, report included

The following paragraphs describe which QGIS project settings are more relevant in relation to the published WebGis service.

9.1 Project property

From the **Project** \rightarrow **Properties** menu, you can access the **Project Properties** window and the three submenus of our interest:

- General
- Data sources
- QGIS server

9.1.1 General

General Settings

In this section it is possible to define the title of the project, consequently the title of the WebGis service.

This title will be used at the G3W-SUITE application level to uniquely identify the published project; for this reason it will not be possible to assign the same name to different projects published on the WebGis service.

We advise against using special characters, or numbers in the project name.



9.1.2 Data sources

The option **Automatically create transaction group where possible** is automatically inherited in the online editing function.

Layers Capabilities

This submenu defines the querable and/or searchable layers at the WebGis service level.

- Check the Identifiable column if you want that the layer will be searchable on the WebGis
- Check the **Searchable** column if you want that the layer will be querable on the WebGis

NB: this differentiation is only possible by using the QGIS APIs such as Search URL endpoint. See dedicated paragraph

80	Project Propertie	s	Data Sources				
⊲ ≫ ≧	General Metadata CRS		Automatically create trans Evaluate default values or Trust project when data so Layers Capabilities	saction groups a provider side ource has no m	where possible	2	
~	Default Styles		Layer	Identifiable	Read-only	Searchable	Required
اللہ میں اور	Data Sources Relations Variables Macros		 Anthropic elements Buildings join Maintenance Roads Work areas Base map CTR multiscale 	V 		V V V	
			Toggle Selection		Show spatial l	ayers only	Filter layers
			Help			Apply	Cancel OK

9.1.3 QGIS Server

Service capabilities

In this section it is possible to define the capabilities of the service.

This information, together with info about the structure of the attribute tables of the layers present in the project, will be displayed in the **Metadata session** of the cartographic client.

See also dedicated paragraph

🔻 🗹 Service Capa	abilities	
Short name	A name used to identify the root layer. The short name is a text string use	d for ma
Title	Schedature aree boscate parchi ed elementi vegetal pregio	
Organization	Comune di Quarrata	
Online resource	The web site URL of the service provider.	
Person	Leonardo Lami	
Position	Publisher	*
E-Mail	Llami@comune.quarrata.pt.it	
Phone	0573 771250	
Abstract	Points of interest	
Fees	No conditions apply	*
Access constraints	None	
Keyword list	List of keywords separated by comma to help catalog searching.	

Capabilities WMS - Advertised extent

In this section it is possible to define the geographical extension displayed when the WebGis service starts.

To define it, set the desired geographical view on the map and then click on the 'Use Current Canvas Extent' button.

▼ WMS ca	 WMS capabilities 						
▼ 🗹 Ad	vertised extent						
Min. X	1652481.17999839526601136						
Min. Y	4852728.6875						
Max. X	1664795.13250160473398864						
Max. Y	4862023.8125						
	Use Current Canvas Extent						

WMS Capabilities - CSR restrictions

In this section it is possible to define the projection systems for which the project is available in relation to OGC services.

It is clearly necessary to insert the projection system on which the project was made, this SR is added by clicking on the **'Used'** button.

Other geographic reference systems can be implemented by clicking on the '+' button and choosing from the list of reference systems.

▼ ✓ CRS rest	ictions		
EPSG:3003 EPSG:4326 EPSG:3857			
* -	Used		

Capabilities WMS - Exclude layouts

In this section it is possible to exclude some of the print layouts that are associated with the cartographic project from the availability of the WebGis service.

A3		

Capabilities WMS - General aspects

Two further aspects are manageable with regard to WMS capabilities

- in general it is recommended to check use the layer ids as names option
- the option **Add geometry to feature response** must be checked to activate the **zoom to the features** on the WebGis service

INSPIRE (European directive)		
Use layer ids as names		
✓ Add geometry to feature response		
Allow defining datasources in server requests		
Segmentize feature info geometry		
GetFeatureInfo geometry precision (decimal places)	8	
Advertised URL		
Maximums for GetMap request		
Width	Height	
Quality for JPEG images (10 : smaller image - 100 : best	quality) 90	•
Default scale for legend	1:1000 -	

WMTS Capabilities

In this section it is possible to define which layers are exposed as WMTS services defining the various options

WFS Capabilities

In this section it is possible to define which layers are exposed as WFS services.

The WFS service is needed if you want activate following types of query:

- Query by bbox
- Query by polygon (rectangle/square)
- Query by draw polygon

It is sufficient to check only the Published column

Layer	Published	recision (deci	Update	Insert	Delete
Frazioni principali		8 🗘			
Gestione scarichi	~	8 🌲			
8 Stradario	v	8 \$			
v_pol_2k		8 2			
0 v_pnt		8 \$			
e lu fa		0 *			

WCS Capabilities

In this section it is possible to define which rasters are exposed as WCS services

9.2 General aspects

9.2.1 Themes (Views)

The creation of **Themes** (combination of off / on layers and differentiated symbology styles) is managed at the WebGis service level.

A specific menu on the webgis will allow you to choose the Theme to be displayed.

The views will be parameterizable at the URL level of the related webgis service.

9.2.2 Layer order

The option to define the layer order different from the order in the TOC on the QGIS project is automatically supported.

9.2.3 Legend

The activation of the **Filter legend by Map content** option on the QGIS project is automatically applied to the derived WebGis service.

If the **Show features count** function is activated in the QGIS project at vector layer level, the same information will be displayed on the web map.

The number of features updates automatically based on the style associated with the layer.

9.2.4 Spatial Bookmarks

In case Spatial Bookmarks are saved at the QGIS project level, they will also be available on the web map.

9.2.5 Mutually exclusive groups

The activation on the QGIS project of the **Mutually exclusive group** option for the layers groups is automatically applied to the derived WebGis service.

9.2.6 1:N and N:M relations

The interface inherits the 1: and N:M relations defined in the **Project Properties** from the QGIS project.

The suite also manages relations based on multiple keys.

ATTENTION: to correctly manage these types of relations it is NECESSARY to insert the reference to the relations in the customized form



9.2.7 Embedded project

It is possible to publish QGIS projects that contain layers or groups of layers deriving from embedded projects. It is clearly necessary to publish the embedded project first and then those derived from it. An update of the embedded project will result in a consequent modification of all derived projects. The request to delete the basic embedded project causes a warning message as this operation will cause problems on all derived projects.

9.3 Layers properties

9.3.1 Simbology

The rendering style associated with the individual layers is replicated autonomously on the WebGis service.

The suite allows the switching on/off of the individual categories linked to the various simbolgy methods (categorized, graduated, by rules \dots).



If external SVG icons are used (added to the basic ones of QGIS, via the **Settings** -> **Options** -> **System** -> **SVG paths**), these must be uploaded to the server (through the **File Manager** tool) in order to be used by QGIS Server.

Manage custom SVG icons

In the installation procedure of the G3W-SUITE application, an **svg** named directory is created on the server.

Within this directory it is therefore possible to store SVG icons, also organized in subdirecory.



The **Configurations icon**, located in the upper right corner of the **Administration Panel**, allows you to access a menu that includes the **File Manager** item.





Through this tool it is possible to manage SVG icons on the server in a simple and intuitive way.



The SVG folder on the server must reflect the structure in any subfolders present locally.

NB: The name of this directory is defined by the basic settings set during the installation of the suite. See dedicated paragraph.

PS: remember that the **File Manager** tool also allows you to manage the synchronization of geographical data (in the case of using physical files) and the management of multimedia files.

See also dedicated paragraph

9.3.2 Multi-style layer

The suite manages the presence of multiple styles associated with a layer.

It will be possible to dynamically choose the style on the cartographic client.

It will be possible to manage the styles associated with a layer from the Administration component, also by **loading** .qml file styles and setting the default style among those present.

9.3.3 Definition of the fields that can be consulted for each layer

Within the QGIS project it is also possible to define, for each layer, which fields are available following query on the WebGis service.

To define these settings, you access the properties of one of the vectors previously defined as searchable and choose the **Source Fields** submenu in the **Layer Properties** window.

This submenu lists the fields associated to the table of the vector.

The check box relating to the **WMS** column defines whether the values contained in this field will be available following the query on the WebGis service.

- 10										
	16 1									
	Id ^	Name	Alias	Туре	Type name	Length	Precision	Comment	WMS	WFS
	123 0	id		int	int4	-1	0		V	V
	123 1	prot_dom	Num. Protocolo	qlonglong	int8	-1	0			✓
	abc 2	data_dom	Data Protocollo	QString	varchar	254	-1		v	<
	abc 3	num_auto	Num. Atto	QString	varchar	254	-1			•
	123 4	anno	Anno Atto	qlonglong	int8	-1	0			v
	abc 5	data_auto	Data Atto	QString	varchar	254	-1		v	•
	abc 6	tipo	Tipologia	QString	varchar	254	-1		v	•
	abc 7	pe	Prat. Edilizia	QString	varchar	254	-1		v	v
	abc 8	pratica_su	Prat. SUAP	QString	varchar	254	-1			v
	abc 9	cognome	Cognome	QString	varchar	254	-1		v	v
	abc 10	nome	Nome	QString	varchar	254	-1		v	v
	abc 11	indirizzo	Indirizzo	QString	varchar	254	-1			v
	abc 12	civico	Num. Civico	QString	varchar	254	-1		v	v
	abc 13	oggetto	Oggetto	QString	varchar	254	-1		v	v
	abc 14	note	Note	QString	varchar	254	-1		v	~

9.3.4 Definition of the attribute display form

For each layer it is possible to define the structure of the attributes form associated with displaying the results following query operations.

On QGIS, we can build a personalized form (query form) by creating thematic tabs and groups and defining the distribution of the individual fields and their aliases.

This structural organization will be replicated directly on the query form on the WebGis service.

The current version of QGIS also handles conditional forms and cascade drill-downs

9.3.5 Layer basic information

If you set a descriptive information in the **Abstract** form of the **QGIS** Server session of the Layer Properties, this information will be associated with the layer at the webgis level.

9.3.6 Temporal settings

This functionality is only available using QGIS Server >= 3.26

The Temporal Controller functions in QGIS are replicated on the webgis component

Time series functionality works on both vector and raster data, even in multi-layer mode.

Time setting on vector data is limited to the Single Field with Date/Time case



Viewing multimedia content

Multimedia contents (images, pdf, web URL ...) can be viewed interactively on the map client following publication of the QGIS project.

In the case of web links, simply insert them (preceded by the prefix **http://** or **https://**) within the dedicated attribute fields

In the case of multimedia files it is necessary:

- upload the media file to the media_user folder (folder exposed on the web) accessible through the File Manager tool in the Suite Administration Panel
- insert the web link to this file in the dedicated attribute field

The link to the file can be obtained in the following way:

• application domain + media_user + path of the file + file name

Example:

- application domain: https://dev.g3wsuite.it
- file file_A.pdf located in the folder /media_user/form/
- web link: https://dev.g3wsuite.it/media_user/form/file_A.pdf

Following queries at the cartographic client level, we will have different behaviors based on the type of content:

- image: preview display in the form, click on the preview to display the image in real size
- web link or other multimedia file: display of an Open orange button to allow consultation of the content

	id	Name	Address	
#	21	Garibaldi Palac	e Via Alfredo	Oria
General Info		Те	chnical data	
Identification		Doc	uments	
id	21	Pho	to	
Name	Garibaldi Palac	e		THE .
Address	Via Alfredo Oria gia' Via Vecchia	ani Data	sheet	Open
Туре	Residential	Link		Open
Year of construct	ion 2006	Cate	oria	B



9.4 Print layouts

Any print layouts associated with the published QGIS project will automatically be associated with the published WebGis service.

Print layouts can contain more than one Map items and panoramic maps.

You can set also a custom title (definible in the WebGis side) setting an Item ID at a Label item.

Atlas and report are also supported.

Any images present in the print layouts must be placed in the local **project_data** folder (in any subdirectory) and synchronized on the server.

See also the dedicated paragraph Geographic data synchronization on the server.

9.5 Performances optimization

9.5.1 Mandatory rules

- PostGreSQL/PostGis, SQLite/Spatialite and GeoPKG layers must have a primary key
- the primary key field and all fields involved in search, join, 1:n or N:M relations or editing function have to be **published as WMS**
- don't use commas for aliases associated with layers
- style settings defined at the auxiliary data level are not supported

9.5.2 Tips

- when using rule-based/categorized classification create indexes on the column(s) involved in the rule expression
- start the project with only a few layers turned on by default
- do not exceed three nesting levels in the groups of layers defined in the TOC

G3W-FRONTEND: THE FRONT END PORTAL

This section describes the different sections of the access portal and how to login to the Administration Panel

10.1 The login portal sessions

The G3W-SUITE application is accessible via any internet browser (FireFox and Chrome recommended) via the URL address defined during installation

If you have also installed the front-end portal from the GitHub repository, access to the application will be via the portal itself.

The home page will contain, in addition to a brief and customizable presentation of the service, also:

- a menu at the top right side with the following items:
 - Change language
 - Go back to the home page
 - Login
- a **panel menu on the right** with the following items:
 - Maps
 - Info



Most of the information shown in the access portal can be defined from the **Configurations** -> **Edit General Data session**, accessible from the icon located in the upper right corner of the Administration Panel.

G3WSUITE

🛪 Frontend 🔒 admin01 English

10.1.1 Info

The Info session can contains a small introduction and contact information for your company or public facility.



10.1.2 Maps

Within G3W-SUITE it is possible to organize webgis services in hierarchical containers (**Cartographic Macrogroups** and **Cartographic Groups**)

By accessing the **Maps** session, the **Macrogroups** (if present) will be displayed, access to the Macrogroup will allow you to view the associated **Cartographic Groups** and from these access the list of individual **WebGis services**.

The MacroGroups, Groups and WebGis services listed will be those defined as free access.

If you have a user for access, you can authenticate yourself through the Login session.

Following authentication, the **Maps** page will also show the MacroGroups, Groups and WebGis services with restricted access and on which the user has access permissions.



10.1.3 Login

If you have a user with login credentials, you can authenticate yourself through this session by entering your user and password.

If you are an Administrator or Editor of 1 or 2 level, you can also access the Administration session.

Once logged in, you access the Admin session and from here, via the "Backend" button to the Administration panel



ELEVEN

G3W-ADMIN: THE ADMINISTRATION PANEL

This section describes how to manage the various aspects and features of the Suite:

- customization of the access portal
- user creation and management (individuals and groups)
- creation of MacroGroups and cartographic Groups and definition of access and management policies
- publication of QGIS projects as WebGis services
- updating and management of WebGis services (search tool and additional functions)

11.1 Description of the interface

The Administration Panel allows you to manage all aspects related to the publication of QGIS projects and configuration of related WebGis services

The main page of the Administration Panel shows:

- a bar at the top:
 - Frontend: to return the landing page portal
 - Username: to edit your profile and log out
 - Language: to choose the interface language

OC.

- A gear icon : to access a menu with:

-> Edit general data: to set information shown in the front-end portal

- -> Django Administration (only for Admin01 user): to configure Django advanced settings
- -> Files: to access the File Manager tool
- a text menu on the left:
 - Dashboard: Administration dashboard
 - Cartographic Groups: to create/manage cartographic groups
 - Macro Cartographic Groups: to create/manage Cartographic MacroGroups
 - Users: to create/manage single users and/or user groups
 - List of active modules: to activate/manage the functional modules active in your installation

- a dashboard in the center of the page
 - Dashboard: to access to list of Cartographic Groups
 - Module list: to access the respective settings

g3w SUITE						English 🛩 📽
IMENU	Dashboard Current situation					🍘 Dashboard
🚳 Dashboard						
Cartographic groups	12					
Macro Cartographic groups <	Groups					
TACL	Show O					
🗃 Users 🗸 👻	Module widgets					
Add user	< Laws 📃	🔋 CDU		Cadastre		-
🔮 Users list	Laws management module	CDU module administratio		Cadastral data m	odule management	
Groups users list					-	
1LAW		= +	PU .	C	o e	·
🖈 Laws 🗸	Laws	Profiles New	Make CDU	Report	Censual Cor	fig
Icou		profile			data	
*						
CDU Contigs <						
ICADASTRE						
🚦 Admin 🛛 <						

11.2 Front end portal customization

From the main page of the **Administration Panel** it is possible to customize the information shown on the Front End Portal.



Click on the **Configurations** icon will appear in the menu below.

located at the right bottom and choose the item Edit general data which



In the General suite data form you can define all the informations that will appear on the portal home page

• Home data: info that will appear on the front end landing page

- About data: info that will appear in the About it session
- Group map data: info that will appear in the Maps session
- Login data: info that will appear in the Login/Administration session
- Social media data: links to the social channels that will appear in the About it it session
- Map Client data: main title to be displayed in the cartographic client bar

11.2.1 Front End Home Data

Informations that will appear on the front end landing page

ATTENTION: contents marked with * are mandatory.

le*				
33W-SUITE				
btitle				
GeoSuite				
me description				
× Β <u>U</u> Ι Β №*	<mark>▲</mark> • ≡	8 E		Θ
8 🚸 🗠 🕫 ?				
				í.
Framework OS dedicato alla	OS Frame	work de	licated t	•
Framework OS dedicato alla pubblicazione e gestione di	OS Frame the public	work de ation an	licated t d	0
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi	OS Frame the public managem	work de tation an tent of Q	licated t d GIS	0
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis	OS Frame the public managen projects a	work de cation an nent of Q ns WebGi	licated t d GIS service:	0
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis	OS Frame the public managen projects a	work de cation an nent of Q is WebGi:	licated t d GIS service:	5
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis	OS Frame the public managen projects a	work de cation an nent of Q us WebGis	licated t d GIS service:	5
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis te logo	OS Frame the public manager projects a	work de cation an nent of Q us WebGis	licated t d GIS service:	5
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis Ite logo	OS Frame the public managen projects a	work de cation an nent of Q is WebGi	licated t d GIS service:	5
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis	OS Frame the public managen projects a	work der cation an nent of Q is WebGi	licated t d SIS : service:	5
Framework OS dedicato alla pubblicazione e gestione di progetti QGIS come servizi WebGis te logo	OS Frame the public manager projects a	work der cation an nent of Q is WebGis	licated t d SIS : service:	5
Framework OS dedicato alla pubblicazione e gestione di progetti QciS come servizi WebGis te logo	OS Frame the public manager projects a	work dee cation an nent of Q is WebGi	licated t d SIS : service:	5
Framework OS dedicato Alla progetti QGIS come servizi WebGis Ite lago	OS Frame the public manager projects a	work dee cation an eent of Q is WebGis	licated t d SIS : service:	5
Framework OS dedicato Julia pubblicazione e gestione di progetti Qelis come servizi WebGis telogo & Chek co g. 32.4KB Delete telogo	OS Frame the public manager projects a	work dec cation an hent of Q is WebGis	licated t d SIS : service:	5



11.2.2 Front End About Data

Informations that will appear in the **Info** session **ATTENTION:** contents marked with * are mandatory.

E Fron	tend	abou	t data																		
About ti	tle*																				
G3W-S	UITE	s a geo	suite a	inimt	istration	n syster	m														
About na	ame*																				
GIS3W	SNC																				
About pl	hone																				
+39 39	3 8534	336																			
About er	nail																				
info@g	gis3w.i	t																			
About ad	idress																				
V.le G.	Verdi -	Monte	catini T	erme	(PT) - I	taly															
About de	escript	tion																			
20	в	U	I		14 •	A	•	=	i≡	≡.	8		99	×	<>>	*	1	?			
G3V	V-Su	ite è	una	solı	ızion	e ide	ata	pe	G	3W-:	Suit	e is a	a sol	utio	n de	esig	ned		^		
sem	nplif	icare	la pi	ubb	licaz	ione	e la		te	o sim	nplif	y th	e pu	blica	atio	n ar	nd		н		
ges	tion	e di s	erviz	i W	ebGi	s da	par	te	m	ana	gen	nent	of W	/ebG	iis s	ervi	ces				
di q	uals	iasit	tipolo	ogia	di u	tente	e pe	r le	b	y an	y ty	pe o	fus€	er an	d fo	or th	e				
più	disp	arat	e nec	ess	ità.				n	ost	disp	arat	te ne	eds							
1.2 mil	(mark				tte d						6						h link				
L IN	masu	ruttu	ra pe		ette d	r pub		.are	1	ne in	111/18	uuc	ture	allov	vs u	o pu	DUSI	1	~		
	100																		*	*	24
								onen									14			X	
	ustein	amo	rmatry	o re	rritori	anc											6				
1		and to be	ntoriale (SIT)	del Com													1			4	•
	tandar • al tecnic	Straciones Le si cittada	lo trambio d la in INTERN	die berg	ne dell	- Tandala		in the second	seren be						200		12			1	
	National Gen	galica tel c	ortest a claib er contenut o	nceluzez prigine		det ritorna							and a second c	-	Queteral		- 6-			6	
		euroheu warrish	n, completan	nents Op cell in he	in Source, lut	rbuta per la Icompili Infi	condivis fuctional	iove dathe	Bancha Da		1	₽	Plazzada (PT)	aWitanad			*				
	 Taggarre 	tazone de transfa e la	ee Saliche ca (tentioric) decumentas	ane dette	Sanche das	Harris -	nd mens	cean a													
	 Is selic 	ore to be	di consultaci	one of or	kogranici e an nalici delle ba	iche Gali	HE35 EA 1	auno	0.00												
		Sec. 1			The second	-					2	-			-					INFO	
		Dag.									-		. 0								

11.2.3 Frontend Groups Map Data

Information that will be displayed in the **Maps** session **ATTENTION:** contents marked with * are mandatory.



11.2.4 Front End Login Data

Information that will be displayed in the Login/Administration session

ATTENTION: contents marked with * are mandatory.



11.2.5 Front End Social Data

Links to the social channels that will be displayed in the About it it session

ATTENTION: contents marked with * are mandatory.

aceb	ok link
f	https://www.facebook.com/gis3w.sas/
witte	rlink
¥	https://twitter.com/_gis3w_
loogle	+ link
G٠	https://plus.google.com/+Gis3wlt
outul	e link
à	https://www.youtube.com/channel/UCDF7Xn_GmNu1vdVssU130Gv
nstag	am link
0	
licke	ink



11.2.6 Map client data

Main title to be displayed in the cartographic client bar

edits		uite								
	dits									
¥* Β <u>U</u> I8 ∺* Α*ΞΞ=* ⊞* ∞ Χ «> ∞ α	10	-								

G3WSUITE G3W-SUITE Demo Building management ≑ Change Map ≜admin01 € Credits English ♥

In the Credits subsection it is possible to define additional text for the publishing aspects.

After filling in the various form, click on the Save button to confirm your choices.

Bave DRedo/Back

11.3 Users and Users Groups management

In the left side menu there is the **Users** item with four sub-items:

- Add user
- Users list
- Add groups users
- · Groups users list

Please note that the Suite is equipped with a dedicated module for the integration of Active Directory users via LDAP.

11.3.1 Add user

Through this form it is possible to insert new users and define their characteristics.

- Anagraphic: first name, last name and email address
- Login: username and password
- User backend
- ACL/Roles
 - Superuser status (Admin1 and Admin2 users only)
 - Staff status: deep administration of the application (Admin1 users only)
 - Main roles (Editor1, Editor2 or Viewer)
 - User Editor groups: any Editor2 user group they belong to
 - User Viewer groups: any Viewer user group they belong to
- User data:
 - Departments and image to be associated with the profile
| System users Stystem users list and property | E Desidorio - Gers - Gerepo |
|--|--|
| Anagraphic | Market CL/Roles |
| First name | Superuser status |
| manuela | Designates that this user has all permissions without explicitly assigning them. |
| Last name | Staff status |
| matta | Designates whether the user can log into this admin site. |
| Email address | Main roles* |
| mmatta@regione.sardegna.it | × Editor Level 2 |
| | Select roles for this user |
| | ore reno group |
| | Select EDITOR groups for this user, only Editor Level 2 can be added |
| | User viewer groups |
| | |
| | |
| | Select VIEWER groups for this user, only Viewer Level 1 can be added |
| | Edited VIEWER groups for this user; only Viewer Level 2 can be added |
| 🔒 Login data | Solited WEWER groups for this user, only Viewer Level 1 can be added
© User data |
| ▲ Login data
Username* | Solicit WENKER grouper for bits usary, only Viewer Level 1 can be added User data Pepartment |
| la Login data
Uuraname*
▲ demo | Select WEWER groups for this same only Versor Lovel 2 can be writted User data Department Department |
| Cogin data Username* deno Required. 150 characters or fevers. Letters, digits and @//t+/coly. | Select WEWEB groups for this same, only Versor Lond I can be added © User data Department |
| Login data Username Username | Select WDRER groups for this same, only Viewer Level 3 can be added |
| I togin data Usersame Main data Isersame Main data Isersame Main data Isersame Isersame | Scient WERKE groups for this card, only Means Land Is an idea within User data Department Avalar Avalar |
| Login data Usersame* | Select WEWER groups for this user, only Viewer Level 2 can be added User data Department Aniar Acian A |

After filling in the various form, click on the Save button to confirm your choices.



11.3.2 Users list

Through this form you can consult the list of enabled users and their characteristics:

- Username
- Roles
- User groups to which they belong
- Associated Cartographic MacroGroups (only for Editor1 users)
- Super user and/or Staff privileges
- Email, name and surname
- Creation date
- Info on user creation (G3W-SUITE or LDAP)

Users											Dashboard	> Users > Users li
OUser												
Show 10	o v e	ntries									Search:	
Actions		It Username	1 Roles 1	User groups	11 Macro groups	11 Superuser	11 Staff 11	Email	11 First name	11 Last name	11 Created 11	Backend
1		admin01				•	٥				07/16/2019	
1	•	demo	Editor Level 2					mmatta@regione.sardegna.it	manuela	matta	02/14/2020	g3wsuite
1		editor1	Editor Level 1						Editor1		08/16/2019	g3wsuite
1	•	editor2	Editor Level 2	Editor Service B					Editor2		08/16/2019	g3wsuite
1		p.claps	Editor Level 2					pierluigi.claps@polito.it	Pierluigi	Claps	11/14/2019	g3wsuite
1		r.pispico	Editor Level 1		ARPA Piemonte			rocco.pispico@arpa.piemonte.if	Rocco	Pispico	10/01/2019	g3wsuite
1	•	ramat	Editor Level 1					info@g-ramat.it	Giuliano	Ramat	10/09/2019	g3wsuite
1		robbygri	Editor Level 2					robbygri⊜hotmaiLit	Roberto	Grisolia	09/06/2019	g3wsuite
1	ŧ	s.grasso	Editor Level 1		PoliTecnico Torin	0		susanna.grasso@gmail.com	Susanna	Grasso	09/27/2019	g3wsuite
1		studiosit	Editor Level 1		Studio SIT						09/18/2019	g3wsuite
Showing 1	l to 10 of 14	entries									Previous	1 2 Next

The icons at the head of each row, allow you to:

Modify: to modify the characteristics of the user
Delete: to permanently delete a user

11.3.3 Add Group Users

Through this form it is possible to create new user groups and define their role. Through this form it is possible to create new user groups and define their role.

It is possible to create only two types of user groups:

- Editor: in which only Editor2 users can be inserted
- Viewer: in which only Viewer users can be inserted

The association between user and user groups can also be achieved at the individual user management level. The association between user and user groups can also be achieved at the individual user management level.

In the specific form for creating user groups, the following info are defined:

- Name
- Role: Editor or Viewer
- Users: list of users belonging to the group

System user groups Stystem users list and property					
₿ Group					
Name*					
Editor Service B					
Role*					
Editor	~				
ESave DRedo/Back					

After filling in the from, click on the Save button to confirm your choices.

Save D Redo/Back

11.3.4 Groups users list

Through this form it is possible to consult the list of enabled user groups, their characteristics and the individual users belonging to the group.

User groups			Bashboard ≥ Users ≥ Groups users list
O User group			
Show 10 v entries			Search:
Actions II Name	11 Role	11 Users	11
💿 🧪 🍵 Editor Service B	EDITOR	Editor2 (editor2)	
📀 🧪 🍵 RESBA	VIEWER		
💿 🧪 🍵 Viewer Service A	VIEWER	Viewer2 (viewer2) Viewer3 (viewer3)	
Showing 1 to 3 of 3 entries			Previous 1 Next

Using the icons at the head of each row, you can:

Show details: to consult the characteristics of the user group
Modify: to modify the characteristics of the group
Delete: to permanently delete a group and therefore association with users belonging to the group itself

11.4 Macro Cartographic Groups

In this section it is possible to view the list of Cartographic Macrogroups, manage them and create new ones.

ATTENTION: use the Cartographic MacroGroups only if you need them.

See chapter Hierarchical organization of WebGis services and types of Users to learn more about this aspect.

For example, you can create a **Macrogroup** to collect a series of **Cartographic Groups** belonging to the same Administration (single Municipality within a Union of Municipalities) or more simply to have main containers that contain second level groupings (Groups).

On the left side menu there is the MacroGroup Cartographic item with two sub-items:

- Add MacroGroups: to create a new Cartographic MacroGroup
- MacroGroups list: to access the list of MacroGroups present

11.4.1 Add MacroGroups

Through this item, available only for the Admin users, it will be possible to create a new Cartographic MacroGroup and associate it with an Editor1 type user who will become its administrator.

Let's see in detail the various sub-sessions of the group creation form.

ACL users

Editor users: you define the **Editor1 user** who will become the **MacroGroup administrator**. This user will can manage the MacroGroup by creating Cartographic Groups, publishing projects and creating Users or User Groups.

General data

- Identification name *: a generic internal identification name (not show in the front end)
- **Title *:** descriptive title of the MacroGroup (will appear in the list of MacroGroups) and, eventually, in the client header
 - Use title for client option
 - Use logo image for client option
- **Description:** the description to be associated with the MacroGroup in the frontend
- Logo img*: the logo to be associated with the MacroGroup in the frontend and, eventually, in the client header

By default, the map client header, for each WebGis service, is composed of:

- main title (if set at General Data management level)
- logo and title associated with the Cartographic Group
- title of the WebGis service

If you select the **Use MacroGroup title and logo for the client** options, the map client header, for each WebGis service, will instead consist of:

- main title (if set at General Data management level)
- logo and title associated with the Cartographic MacroGroup
- title of the WebGis service

After compiling the form, click on the Save button to confirm your choices.

Save DRedo/Back

11.4.2 MacroGroups list

The menu provides access to the list of cartographic macro-groups present.

Cartographic macro groups		> MACRO groups list
STUDIOSTI	ARPA Piemonte Agenzia Regionale	at the

There are a series of icons to access specific functions:

	0	
•		Show the details of the MacroGroup
•	/	Change characteristics of the MacroGroup
•	Î	Delete MacroGroup

ATTENTION: the removal of the Cartographic MacroGroup group will result in:

- the removal of all the Cartographic Groups contained in it
- the removal of all the cartographic projects contained in the individual Groups
- the **removal of all the widgets** (eg searches) that would remain orphaned after the removal of the cartographic projects contained in the group. See the Widget chapter for more information.

Define the MacroGroups order on the FrontEnd

Through the Drag & Drop function it is possible to define the order of the MacroGroups in the list. This order will be reflected in the FrontEnd.

11.5 Cartographic Groups

In this section it is possible to view the list of Cartographic Groups present, manage them and create new ones.

A Cartographic Group is create to **collect a series of cartographic projects belonging, for example, to the same theme** (Urban Planning Regulations, tourist maps ...) and characterized by the same projection system.

It should be remembered that it will be possible to switch from one webgis service to another, leaving the same geographical extension and scale, only between the projects contained in the same cartographic group.

In the left side menu there is the Cartographic Groups item with two sub-items:

- Add Group: to create a new Cartographic Group
- Group List: to access the list of groups present

You can also access the list of groups by clicking on the "Show" button in the Cartographic Groups box on the Dashboard.

11.5.1 Add Group

Through this item it is possible to create a new Cartographic Group.

During creation, some functional characteristics and tools that the WebGis interface will show for all cartographic projects published within the group are also defined.

Let's see in detail the various sub-sessions of the group creation form.

General data

- Name *: a generic internal identification name (not show in the front end)
- Title*: descriptive title of the Group (will appear in the list of Cartographic Groups)
- Description: description of the content
- Language*: interface language

Logo/Picture

- Header logo img*: the logo to be displayed in the header del client cartografico
- Use logo image for client option
- Logo link: a eventual link to associate with the logo

REMEBER

By default, the map client header, for each WebGis service, is composed of:

- main title (if set at General Data management level)
- logo and title associated with the Cartographic Group

• title of the WebGis service

If you select the **Use MacroGroup title and logo for the client** options, the map client header, for each WebGis service, will instead consist of:

- main title (if set at General Data management level)
- logo and title associated with the Cartographic MacroGroup
- title of the WebGis service

If you select the **Use Group logo for the client** options, the map client header, for each WebGis service, will instead consist of:

- main title (if set at General Data management level)
- title associated with the Cartographic MacroGroup
- logo associated with the **Cartographic Group** (if MacroGroup logo option is active this options takes precedence)
- title of the WebGis service

ACL Users

Access and modification powers are managed.

The options present will vary according to the type of user (Admin or Editor1) who creates/manages the Group

- Editor1 User: defines the user (Editor1) manager of the Group. The entry is present only when the Admin type user creates the Group If the Group is created by a user of type Editor1, the Group is associated directly with that user
- Editor2 User: defines the user (Editor2) manager of the Group.
- Viewers users: define the individual users (Viewers) who have the credentials to view the contents of the group. By choosing the anonymous user (AnonymousUser) the group will be free to access
- Editor user groups: define the user groups (Editor2) who manage the Group.
- Viewer user groups: you define the user groups (Viewer) which have the credentials to view the contents of the group.

The option **Propagate viewers user (single and groups) permissions** allows you to propagate the Viewer users (individuals and/or groups) associated to the Group to ALL the WebGis services present in it.

This option cancels any differentiation in the access policies applied to the WebGis services contained in the Group.

ACL Users	-
Editor1 user	
******	~
Editor2 user	
Editor2 (editor2)	~
Viewer users	
× Viewer1 (viewer1) × Viewer4 (viewer4) × (AnonymousUser)	
Editor user groups	
× Editor Service B	
Viewer user groups	
* Viewer Service A	
Propagate NEW viewers and new viewers user groups permissions	

MacroGroups

Possible definition of the belonging MacroGroup.

This option is available only if Cartographic macro groups have been created

In the event that the Group is created by an Editor1 type user, the Group will be automatically associated with the MacroGroup associated with the same Editor1.

GEO data

Projection system associated with the group.

N.B. All projects loaded into the group must be associated with this SRID.

Base layers and Map interaction tools

In this box you can define:

- **Mapcontrols***: list of tools available on the WebGis client:
- zoomtoextent: zoom to the initial extension
- zoom: zoom in and zoom out
- zoombox: zoom tool based on drawing a rectangle
- query: puntual query of geographical layers
- querybbox: query via bounding box (N.B. it is necessary that the layers are published as WFS services on the QGIS project)
- querybypolygon: it will be possible to automatically query the features of one or more layers that fall inside a polygonal element of a guide layer. (Eg what's inside a cadastral parcel?) N.B. it is necessary that the all the layers involved in this kind of query are published as WFS services on the QGIS project
- querybydrawpolygon: query based on a polygon drawn on the map (N.B. it is necessary that the layers are published as WFS services on the QGIS project)
- zoomhistory: undo/redo tools to navigate previous and post visualization areas
- overview: presence of a panoramic map
- scaleline: presence of the scale bar
- scale: tool for defining the display scale
- mouseposition: display of mouse position coordinates
- geolocation: geolocation tool (available only with https certificate)
- nominatin: address search tools and toponyms based on OSM
- streetview: Google StreetView on your map
 - in the presence of GoogleMaps API Key, StreetView it is integrated on the client and synchronized with the position and direction of the icon on the map
 - in the absence of GoogleMaps API Key, StreetView it will open on a new browse tab without the aspects of synchronization with the map
- length: linear measuring instrument
- area: surface measuring instrument

- **addlayers:** tool for temporarily uploading GML, GeoJson, KML, GPX, SHP (zipped) and CSV with coordinate to WebGis. These layers will remain until the end of the work session
- screenshot:* tool to take a screenshot of the map area
- GeoScreenshot:* tool to create a GeoTIFF of the map area
- Baselayer: choice of the base maps that will be available on the WebGis client
- Background color: choice of the background color of the maps (default white)

*NB: the security protocols prevent the creation of screenshots if WMS services with domains other than the publication one are present on the map. In this case the icons will not be present on the client even if the MapControl is selected. To avoid this, set the WMS as internal WMS in the Widget managment session.

Base Layers and	I Map default featur	es		
Mapcontrols*				
× zoomtoextent	× zoom × zoombax	× query × q	uerybbox 🛛 × que	erybypolygon
× overview × sca	leline × geolocation	× streetview	× nominatim	× addlayers
× length × area	× mouseposition	× scale × scree	enshot	
Baselayers				
× OSM (OpenStreetM	ap) × Bing Streets (B	ling Streets)		
× Bing Aerial With La	bels (Bing Aerial With Lab	pels)		
Background color				

With regard to the **Base Layers**, it is specified that the external services available by default are:

• OSM

It is also possible to add **Bing** and **Google** maps to the Base Layers but it is first necessary to acquire the respective API Keys and set them in the Django settings level.

Remember that it is possible to build customized Base Layers starting from projects published on the suite.

In this regard, consult the session Base map layer

It is possible to create/add **customized Base Layers** starting from the cache of the single layers present in published webgis

See Caching layer paragraph in the Widget management session.

Copyright

Terms of use: description of the terms of use of the map and any other info Link to terms: link to text

After filling in the various form, click on the Save button to confirm your choices.

Save DRedo/Back

11.5.2 Geocoding map control use case for populating project layers

A specific editing function is associated with the Geocoding map control.

In fact, it is possible to use the results deriving from the providers associated with this map control (OSM, Bing Streets, Bing Places) to populate point layers present within the webgis service.

Below are the settings and steps to perform for this purpose.

Activation of Geocoding map control at Cartographic Group level

First of all, **Geocoding** must be associated with the Cartographic Group by selecting it at the **Base Layers and Map default features** session level. This will ensure that the tool is present on all WebGis services published within the Group.

Geocoding providers							
× Nominatim (OSM)	× Bing Streets	× Bing Places					

Definition of the providers to use for each WebGis service

In the publication form of your QGIS project you need to define the providers to be associated with the Geocoding map control:

- Nominatim (OSM): addresses based on OpenStreetMap
- Bing Streets: Addresses based on Bing maps
- Bing Places: places based on Bing maps (service available only for the USA)

The association is created at the Geocoding providers session level.

The use of the providers Bing Streets and Bing Places requires the acquisition of a free Bing API.

See Settings section for the API key definition.

Using the Geocoding map control on the WebGis service

The Geocoding tool allows you to search for addresses and places (based on active providers) and view their position on the map and the associated information on the information panel on the right.

It is possible to load markers relating to multiple searches into the map.

≡ caffè	X Q 👅 🕸 🗉	Venue	• B Con	Tower	Building to 621	Civic Square	l latter of	Correcti Carl	Results Geocoding	+ ÷ ×
Bing Pla	res	, i	E IN P	705	P 611	E.	Ath Ave 500		Geocoding (1)	B -
v 🗹 🧳	Restaurant Caffo Limbria Potail	Dai	P P	Cherry Street	Couppers 215-50	James St & 3rd Pigneer Ave	Perfersor	Street (i)	9 🖬 🖉	
Dun	Cane oniona Netan	29 625	100 Mar 627 .	+ 61		Square King Coun	ty 8 422	Building	name	Caffe D'arte Pioneer Square
S 🖌 🕴	Restaurant Coffo D'arto Rionoor Equara	617	610 E P		114 . 520	W Real	City Hall	ouley	lon	-122.33483124
	Calle D'arte Florieer Square	/2mg	Travelers 606	1	mes 2	214	Park Not The		lat	47.60160446
	LocalBusiness	Seattle	Hotel		501 20.	. m I	Outro Ling		type	Restaurant
WA :	304 → Colman Dock	E Square	Yesler y 8	Vesi	155 • 427	Yesler Way 221 233		Yesi	address_road	99 Yesler Way
APPENDING NO.		skan	Pioneer 91	eoge 1	07 : 423	Frye Apartments			address_postcode	98104
- the second	Pianeer Square	5 keN	Hotel	10 See	116	117 I	4Culture	0 5	address_city	Seattle
lest Seattle, Vashon		+ un		Paulo 1	21 403	I An W		Fire Station No.10	address_state	WA
land Water Taxi	King County				South Washington Street	H H	I-Q-118		address_country	US
	Maintenance	SR 99	208 🙀 201		210 207	220 Clenta	S Washingfort	P P	address_formatted	99 Yesler Way, Seattle, WA, 98104
) Tunn	Center Lucky OK Hotel Hotel	Tsonqua (Totem)	Building 215	220 B	210	200	bing type	SearchResult:http://schemas.microsoft.com/search/local
101 2	301	ē t	80 Main 94 🔤 🖡	· *	1 150 224 Waterfall	Ŷ 240 	222	Place 450	Sup_type	/ws/rest/v1
101 -		8 8	····· ×····· 81	South Mai	in Street X	×·····×··	8××8	South Main Street	bing_name	Caffe D'arte Pioneer Square
		† G	304 P	Trust	306 Seattle	P Building	S Main K&-3rd	Addison on Fourth	bing_point_type	Point
		SR 99 Tu	74 • AX	Square	Fire Departm	315 317	P III	316 Icon	bing_point_coordinate: _0	47.60160446
		0	South Jackson Street	102 108	155 • B 163 •	212 321			bing_point_coordinate: _1	-122.33483124
с	* P	Ť	403-05 Alaskan	109 Aalle 410	410 171 Court in the	Metro Transit Information Office			bing_Address_address ne	i 99 Yesler Way
		\$2+	423 H	110 Sou	Graybar Building th King Street	P P		n Ave Spikson St	bing_Address_adminDi trict	⁵ WA
		B9 Tunne	99 Seattle Hardware	101 King Street	Stadium 501	Stadium	Art-st-King Street Station	District/ Chinatown 505 Union	bing_Address_country egion	t us
	499	WA 99	Building 541	524 528	30	Embassy Suites Seattle	Scattle	Station 550	bing_Address_formatte dAddress	99 Yesler Way, Seattle, WA, 98104
		1	Aven 243	515		Pioneer	8	17.00	bing_Address_locality	Seattle
		- SR 99	SR-99 Tunnel Operations	536 540 567 97		Charger		605 Un 50 m	bing_Address_postalCo de	98104
G3WSUITE © Op	enStreetMap contributors.				1-4120	- X: 136	18616.0525 Y: 6041079.8	068 [EPSG:3857]		

On the right of the search tool there will now be three new icons:

- Clear markers selection: to delete all markers inserted on the map
- Toogle markers visibility: to activate/deactivate the display of markers
- Toogle sidebar panel: to view the list of markers loaded in the map and their attributes on the right panel

caffè 🗙	۹		Ø	в
---------	---	--	---	---

Insert the markers present in the map into a vector layer

This function allows you to insert the results, obtained through the Geocoding map control, at the level of one or more layers, exclusively point-like, present in the WebGis service.

To be able to carry out this operation, the online editing functionality must be active on these layers.

Only in this case will there be a pencil icon at the search results level.

Clicking on this icon will show the list of point layers on which online editing is enabled.

After choosing the layer on which to insert the result, click on the pencil icon to the right of the layer name to determine the insertion of the point on the layer itself.

5		→ # ×
		9 🖬 –
lon	lat	+
-122.33065563	47.59829762	
to add this feature		
		▲ 🖉
		+
	lon -122.33065563	lon lat -122.33065563 47.59829762 to add this feature

On the right, the information panel will open which will show the attributes of the self-editing layer filled in only to the fields of the same name as those of the source markers.

esults / m	ultipoint_la	ayer		
Editing	attribute	s mul	tipoint_	layer
fid *				
Autogene	rate			
name				
Caffe Um	bria Retail			
type				
Restaurar	nt			
address_fo	rmatted			
320 Occid	lental Ave S, S	eattle, V	VA, 98104	
provider				
bing_plac	tes			
	* Req	uired fi	elds	
	nsert/Edit	Igno	ore Changes	

By clicking on the green Insert/Edit button the point will be permanently saved on the layer in use.

11.5.3 Groups List

From this item you can access the list of the created cartographic groups.

For each group, the Title and Subtitle defined at the time of creation are shown.

There are also a series of icons to access specific functions:

Add a new project to be published on the WebGis service
Number and links to projects published within the Group
Show group details

Change group characteristics

• **Delete** group

ATTENTION: the removal of the cartographic group will involve:

- the removal of all the WebGis services contained therein
- the **removal of all widgets** (eg searches) that would be orphaned after the removal of the WebGis services contained in the group. See the Widget chapter for more information.

A large + icon is available to access the form for creating a new group.



Cartographic Group Trash

The operation of deleting a Cartographic Group is not definitive.

The Group with all its related content (projects and widgets) is moved to the Trash session.

It is possible to access the list of trashed.

Cartographic Groups and the restore functions through the menu on the left sidebar.



Restoring a Cartographic Group involves restoring all the projects it contains and all the accessory settings/functions of both the group and the projects (permissions, searches, editing settings, downloads, etc...).

Deleting a Cartographic Group from the trash is an irreversible action.

Define the Groups order on the FrontEnd

Using the Drag & Drop function it is possible to define the order of the Groups in the list.

This order will be reflected within the belonging MacroGroups.

NB: currently in the list of Groups it is not present in the subdivision in the belonging MacroGroups but the fact that a Group can be associated with only one MacroGroup still allows you to manage intuitively what will be the complessive display order.

11.6 Publication of new WebGis services

11.6.1 To publish a new QGIS cartographic project

It is possible to publish new QGIS projects:

- from the list of cartographic groups: click on the icon in which you want to publish the project.
- from the list of cartographic projects published within a group: by clicking on the the button + royar QQ

In the dedicated form we could define the characteristic of the project being published:

QGIS project

QGIS file*: load the QGIS cartographic project to be published (.qgz or .qgs file)

ACL Users

Management of access and/or modification permissions

The options present will vary according to the type of user (Admin, Editor1 or Editor2) who creates / manages the WebGis service.

• Editor1 user: defines the user (Editor1) manager of the WebGis service.

The entry is present only when the WebGis service is created by Admin or Editor1 user.

In the event that the WebGis service is published by a user of type Editor1, the WebGis service is associated directly with that user

• Editor2 User: defines the user (Editor2) manager of the WebGis service.

The item is present only when the user of the Admin or Editor1 type creates the service WebGis. In the event that the WebGis service is published by a user of type Editor2, the WebGis service is associated directly with that user

- Viewers users: define the individual users (Viewers) who have the credentials to view the WebGis service. By choosing the anonymous user (AnonymusUser) the group will be freely accessible.
- Editor user groups: define the user groups (Editor2) who manage the service.
- Viewer user groups: you define the user groups (Viewer) which have the credentials to view the content of the service.

ACL Users	-
Editor1 user	
Editor1 (editor1)	~
Set Editor Level 1 owner	
Editor2 user	
Editor2 (editor2)	~
Viewer users	
× Viewer1 (viewer1) × (AnonymousUser)	
Editor user groups	
* Editor Service B	
Viewer user groups	
× Viewer Service A	

located under the box of the cartographic group

Default base layer

In this session you define which base layer should be active at startup.

The choice is limited to the list of base layers activated for the cartographic group in which you work.

It is also possible not to define any active base layer at startup.

Description data

- Public title: title of the WebGis service, it will appear at the font end level and in the header of the client.
- **Description:** Description of the project, it will appear at the public portal level.
- **Thumbnail (Logo):** logo to associate with the project. This image will be viewable in the list of projects within the cartographic group
- URL alias: a human readable URL for the map. Only alphanumeric characters, not white space or special characters.

The title associated with the WebGis service is inherited by the following settings evaluated in the following order of priority:

- Public title: if set
- QGIS project title: if set on the General session of QGIS project properties
- Name of the QGIS project file

Options and actions

• User QGIS project map start extent as webgis init extent: check this control if you want set initial extent from QGSI project initial extent

Otherwise the initial extension will correspond to the maximum one defined on the basis of the extension associated with the WMS capabilities of the QGIS project (**Project properties -> QGIS Server -> WMS capabilities (Advertised extent)**)

• Tab's TOC active as default: set tab's TOC (Layers, Base layers, Legend) open by default on startup of

•

- webgis service
- **Tab's TOC layer initial status**: it is possible to define whether the TOC layer list is collapsed or expanded when the WebGis service is started
- Map themes list initial status: it is possible to define whether the list of themes (views) possibly associated with the project is collapsed or expanded when the WebGis service is started
- Legend position rendering: this option allows to set legend rendering position:
 - In a separate TAB: default value, the legend is rendered into a separate tab
 - Into TOC layers: the legend is rendered inside layers toc
- Automatic zoom to query result features: if in the results of a search there are only features of a layer, the webgis automatic zoom on their extension

The next options allow you to define the type of WMS / WFS query to be carried out and the maximum number of results obtainable following a query.

• Max feature to get for query*: max number of feature to get for single or multiple mode

- Query control mode*: single or multiple
- Query by bbox control mode*: single or multiple
- Query by polygon control mode*: single or multiple

In the last box you have to define the providers to be associated with the Geocoding map control:

- Geocoding:
 - Nominatim (OSM): addresses based on OpenStreetMap
 - Bing Streets: Addresses based on Bing maps
 - Bing Places: places based on Bing maps (service available only for the USA)

Enabling providers is carried out at the general application settings level.

ATTENTION: contents marked with * are mandatory.

QGIS projectPublic building management Spatialite	🏶 Dashbaard > Cartographic groups > Projects list G3W SUITE Demo > Update QGIS project g3w suite-demo public-building-management spatialite
Shortcuts	
m Show man A Show datail I = Lawars	
盦 Ogis Project	👗 ACL Users —
	Editor1 user
i î A filo une.	V
	Set Editor Level 1 owner
Lick of Drag hie to Upload	Editor2 user
<u>i</u> i	v
projects/g3w-suitespatialite.qgs	Viewer users
	× (AnonymousUser) × (viewer1)
	Editor user groups
	Viewer user groups
Default base layer	
Base Laver	
OSM (OpenStreetMap)	
Description data	Options and actions
Public title	User QGIS project map start extent as webgis init extent
Official demo	Tab's TOC active as default*
Description	Layers
$\not\succ \bullet \mathbf{B} \underline{\mathbf{U}} I \mathbf{\mathcal{B}} \boldsymbol{\mathbf{\mu}} \bullet \underline{\mathbf{A}} \bullet \equiv \equiv \equiv \equiv \bullet \boxplus \bullet \boldsymbol{\mathbf{\infty}} \mathbf{\mathcal{M}} \bullet \mathbf{\mathcal{M}} $	Set tab's TOC open by default on init client
An example of cartographic management rich in analytical functions, researches, graphs and much more.	Legend position rendering*
To test the features and power of online editing, log in with the following credentials	In a separate TAB v
• user viewer1 • pwd: G3wsuite123	Set legend position rendering
	Automatic zoom to query result features Automatic zoom on query result features for only one laver
	Max feature to get for query*
	5
	Query control mode*
Thumbnail	Single
[Query by bbox control mode*
▲ Click or Drag file to Upload	Single
	Query by polygon control mode*
building.one	Single
URL attas	
You can set a human readable URL for the map. Only alphanumeric characters, not white space or special characters	
the second characteristic second characteristic conductors, not mine speece or special characteristic	
R) Cause - 10 Dade (Dade	

After filling in the various form, click on the Save button to confirm your choices.

Save DRedo/Back

If the operation is successful we will see the new project appear in the list of projects in in the working Cartographic Group.



11.6.2 Embedded project

It is possible to publish QGIS projects that contain layers or groups of layers deriving from embedded projects. It is clearly necessary to publish the embedded project first and then those derived from it. An update of the embedded project will result in a consequent modification of all derived projects. The request to delete the basic embedded project causes a warning message as this operation will cause problems on all derived projects.

11.6.3 Define the WebGis order on the FrontEnd

The order of the WebGis services listed within the Thematic Group at the FrontEnd level reflects the order defined at the level of the corresponding administration session. It is possible to define a custom order by moving the published projects via drag&drop.

11.7 Update/ Manage WebGis services

To **update** a published WebGis service, access the list of projects in the Cartographic Group.

Click on the **Edit** *i*con placed at the top of the WebGis service and reload the QGIS file with the changes made in the relevant form.

Click on the **SAVE** button to confirm the change.

Always starting from the list of WebGis services, it is possible to manage numerous functional aspects associated with them.



11.7.1 Basic tools

In this section it is therefore possible to view the list of cartographic projects present, view them, manage them and create new ones.

Through the single icons, placed at the level of each project, it is possible to:

- **Display the cartographic project on the WebGis interface:** to check the display by the user
- = Access the list of layers present within the project and define their functional aspects
- Show details: for each WebGis service it will be possible to access a detailed summary that will list all the activated settings and widgets:
 - access and modification permissions
 - the list of active searches
 - editing permissions on individual layers
 - definition of alphanumeric and geographical constraints
 - visibility constraints on layers
 - visibility constraints on attribute fields
 - **Test the WMS Capabilities** of the project
- **Update a project:** update of the QGIS file and other options related to the project
- Remove a cartographic project Warning: removing a project also removes all the widgets (e.g. searches) that would be orphaned after the project has been removed
- Download of the QGIS project
- S List of OGC services associated with the project
- 9 Messages the tool allows you to define personalized (timed) messages visible when the WebGis service starts

Below are some insights into specific features

Show details

A useful tool for having a summary of all the settings and functions connected to the project.

×		
	Editing	Editing prop
	Layer:	Layer: Mair
	Scale: User addi User editi Usernar viewer1	Scale: User adding dat User editing dat Username viewer1
	Layer:	Layer: Buil
	Scale: User addi User editi	Scale: User adding dat User editing dat
	Usernar	Username
	viewer1	viewer1
	Layer:	Layer: buil
	Scale: 1:2	Scale: 1:2500
	User addi	User adding dat
	User editi	User editing dat
	viewer1	viewer1
	viewer2	viewer2
	1	1
	Layer:	Layer: road
	Scale: User addi	Scale: User adding dat
	User editi	User editing dat

Messages

The tool allows you to define personalized (timed) messages visible when the WebGis service starts.

By clicking on the icon, the messages associated with the service are displayed.

+ Message				
Show 10 v entries		s	earch:	
Actions	↓≞ Title	Lî level L	Availble from	Available to
/ =	test	Error	May 1, 2023	May 31, 2023
/ =	Happy mapping with G3W-SUITE	Info	April 12, 2023	Dec. 31, 2023
Showing 1 to 2 of 2 entries			Previous	1 Next

Using the + Message key it is possible to create a new message by defining:

- title
- message body (also in html)
- message type (info, warning, error, critical)
- validity period (optional)

New Message	Bashboard > Cartographic groups > Projects list G3W-SUITE Demo > Update QGIS project's message g3w-suite-demo public-building-management-demo
🔓 General data	Validity
Title*	Valid from
Happy mapping with G3W-SUITE	
Set the main title of the message	Starting date of message display
Body*	Valid to
$\not > \mathbf{B} \ \underline{\mathbb{U}} \ I \ \underline{\mathcal{B}} \ \underline{\mathbb{H}}^{*} \ \underline{\mathbb{A}} \ \underline{\mathbf{v}} \ \Xi \ \underline{\Xi} \ \underline{\Xi}^{*} \ \underline{\boxplus}^{*} \ \underline{\Theta} \ \underline{\times} \ \underline{\phi} \ \underline{\mathbf{v}} \ \underline{\sigma} \ \underline{?}$	2023-12-31
	Ending date of message display
G3WSUITE	
Example of cartographic management product with QGIS and G3W-SUITE.	
Management of buildings, their value over the years and related maintenance interventions. Manage public builds and registering individual maintenance interventions.	
The suite allows you to automatically inherit from QGIS project:	
project and layers properties and capabilities inite and LM relation	
plots create with DataPlotly QGIS plugin	
print layouts (simple and atlas) query and editing form	
editing constraints and widget	
_	
Set the body of the message	
Level*	
Info v	
Select level of message	
🖹 Save 🖸 Redo/Back	

Project Trash

The operation of deleting a Project is not definitive. The Project with all its related content (widgets and settings) is moved to the Trash session.

It is possible to access the list of trashed Projects and the restore functions through the tab Trash positioned just above the list of published projects

+ Project QGIS				
E Projects Trash (1)				
Actions Logo	QGIS project title	Public title	URL alias	Created/Modified
	Big data			created: Feb. 20, 2021, 11:14 a.m. modified: March 23, 2023, 12:11 p.m.

Restoring a Project involves restoring all the accessory settings/functions of the project (permissions, searches, editing settings, downloads, etc...).

Deleting a project from the trash is an irreversible action.

11.7.2 Setting up the overview map for WebGis services

In this session it is also possible to define which of the cartographic projects loaded within the group will be used as a panoramic map.

To set the panoramic map, choose the projects and tick the check box in the **Overview** column.

11.8 Widget management

Once a cartographic project has been published, though the icon = it is possible to access the list of the geographical states that compose it and define some functional aspects that will be enabled at the cartographic client level.

Q	GIS Project Layers			🙆 Dash	ooard > Cartographic grou	ps > Projects list G3W-SUITE Der	no 🗧 Layer list QGIS pr	oject g3w-suite-de
ł	Project							
	Public building management An example of cartographic managem To test the features and power of onlin .user: viewer1 .pwd: 63wsuite123	Demo entrich in analytical functions, researches, graphs and much m ne editing, log in with the following credentials	ore.					
	ttt Show map Show detail Edit							
ľ	Data 🖾 Structure							
	Show 10 v entries					Se	sarch:	
	Label JE	Name	î Type 🕼 WMS External 👃	† WFS 👫 Actions		Download It capabilities	Not show attributes ↓↑ table ↓↑	No legend]]
	buildings	buildings 오	1	° •	8 🖻 🖪 🛛 8 🖿 🖓 T	Download		
	Buildings rating	buildings_rating •	/	2 🗑	₽ ₽₽₽₽	B Download		
	Maintenance works	maintenance_works 👁	/	2 😫	■ ¶ ■ 8	∎ ▲ Download		
	roads	roads ♥	/	° •	8 🛋 🛄 T	Download		

Next to each layer are a series of icons and checkboxes:

- Label: layer alias applied at the QGIS project level
 - The eye icon allows you to know the ID associated with the layer at the project level, this ID will be useful for creating parameterized URLs
- Name: name of the layer (file or DB table)
- **Type:** illustrates the type of data (WMS, PostGis, SpatiaLite, GDAL / OGR ...)
- WMS external: to speed up loading, the WMS layers present in a QGIS project are managed directly by Django and not by QGIS-Server.
 - In case of non-external WMS, the service is managed by Django and this eliminates cross-domain problems but the only managed GetFeatureInfo response type is GML.
 - The external WMS option allows obtaining a response to the query (GetFeatureInfo) even if the response is not in GML but also in HTML or text/plain format.
 - The option is available only if the WMS loaded on the QGIS project is associated with the same projection system as the project.
- WFS: a check mark shows whether the layer is published as a WFS service or not
- Actions: a series of icons dedicated to various functions

level

Caching Layer: allows you to activate and manage the cache of the single layer at the project *rel*

Editing layer: shows if the online editing function is active on the layer and allows you to activate and define it

- **Hide layer by user/groups:** hide specific layers from the TOC based on specific users or groups of users

- Geo-constraints by user/group: create or manage editing and visualization geo-constraints based on poligonal layers

- Alphanumeric and QGIS expressions constraints by user/groups: create or manage editing and visualization constraints based on SLQ language or QGIS expressions
- **Hide columns by User/Groups:** create or manage constraints on one or more fields of a layer based on single or group user/s
- Widgets list: shows how many widgets (eg searches) are associated with this layer and allows you to activate new ones

2

Manage layer styles: manage multi-style layer

- Download: allows the download of the geographic and not geographic layers in various formats
 - Download as shp/geotiff: for vector and raster layers
 - Download as GPK: for geographic or not geographic layers
 - Download as xls: for all types of layers, in .xls format
 - Download as csv: for all types of layers, in .csv format
 - Download as gpx: for geographic layers, in .gpx format
- Not show attributes table: hide attributes table of the layer for every users
- No legend: it allows to define if the layer must have published the legend at TOC level of the WebGis client

The number above each Action icon shows if and how many related objects are present.

The functions present in the Actions session are described below.

11.8.1 Caching layer (Base Map)

With this icon it is possible to **activate/manage the cache of the single layers** and **create XYZ Tiles layer** that you can use as **Base Layer** in your webgis.

The form allows you to:

- Active: enable cache on the layer
- Action:
 - Reset cache: limited to the specific layer

- Reset cache for project: reset cache of all the layers in the project

If the published project contains only one layer is it possible to convert this WebGis service into a Base Layer.

To do this you need to activate the Base layer option form and fill in the second part of the form:

- Base layer title
- Base layer description
- Base layer attribution

The newly created base layer will be available to be associated with those available for the various Cartographic Groups.

11.8.2 Editing layer

Through this icon it is possible to activate the online editing function on the individual layers and define the permissions for individual / groups of users

See the dedicated paragraph in the Editing on line session.

11.8.3 Hide layer by user/groups

With this icon it will be possible to define the list of users (single and/or groups) who will be enabled to view this layer at the TOC and map level.

Hide layer by User/Groups

Select viewers with 'view permission' on project that can view layer:

Viewers

× (AnonymousUser) × (viewer1)

Select/Unselect user with viewer role can view the layer

User viewer groups

Select/Unselect viewer groups can view the layer



×

11.8.4 🖿 QPlotly widget

View plots created using QGIS DataPlotly (a great plugin developed by Matteo Ghetta) in the cartographic client.

The module, based on the Plotly library, manages plots saved as xml.

The plots are connected to the layers defined on the QGIS project, in this way, as for the searches and the constraints, it is possible to activate (checkink the **Linked** checkbox) the same plots on all WebGis services in which the reference layer is present.

It is also possible:

- download the plot XML file to reuse it in QGIS
- define the activation status of the plots when the WebGis service is started

Label	👫 Name	↓↑ Type ↓↑ WMS External	1 WFS 1 Actions	No 11 legend 11	Download as shp	Download as Download gpkg It xls	l as Download as Download as lt csv lt gpx lt
Buildin	gs buildings 👁	/	≘ Ø % 🛋 T \$ Ø				۵
	• New oplotly widget						
	Actions	Active on startup	Title		Туре	From project	Linked
	/ 📋 🚸		Type distribution		pie		
	/ 📋 🚸		High-Year by type		bar		
	/ 📋 🚸		Year - Volume		scatter		

The title of the chart, defined at the plugin level, will be the unique identifier.

At client level, it will be possible to filter plots based on the geometries visible on the map and/or selected by the user.





Charts based on 1:N data relation (child layer)

If the chart is linked to a child layer in a 1:N relation, it can also be displayed at the information level of the individual parent features



11.8.5 Display and editing constraints

Through the **Geo-constraints by user/group** and **Alphanumeric and QGIS expressions constraints by user/groups** widgets it is possible to define editing and display filters for users authorized to consult/edit the project.

See the dedicated paragraph in the Editing on line session.

11.8.6 Hide columns by User/Groups

Thanks to this function it is possible to hide specific fields of a layer for consultation. This constraint can be differentiated for individual users or groups of users.

This setting is also available for the AnonymousUser user

To activate this type of constraint, you must click, at the level of the layer of interest, on the Hide columns by User/Groups icon .

Clicking on the icon will show the list of any existing alphanumeric column constraints and the item + Create New Column Level constraints to create a new one.

Label	41	Name	『 Type 』 WMS Extern	nal 🗄 WFS 🕸	Actions		II	Not show attributes table 11	No legend 👫	Download as shp/geotiff	Download as gpkg
buildin	gs	buildings 🍄	1	٥	₽ 2 2 ₩ ✓	₽.₽ Lat	<mark>8 8</mark> ∰ \$				
	• Crea	ate New Column Level	Constraint								
	Action	ns	User				Group	•		Restricted	Fields
		/	AnonymousUser							address,pho	ito

Clicking on the item will open a modal window which will allow you to define:

- user or group of user
- list of fields to hide to them

Once all the constraints have been setted, click on the OK to confirm the rules.

11.8.7 🍄 Widget setting - Search tools

Using this icon it is possible to associate a series of widgets to the layer. The basic widget allows you to define search tools that will be available in the webgis.

Basic settings

In G3W-SUITE it is possible to create search widgets.

By default, searches can be built on individual vector layers based on the fields of the table associated with the layer.

NB: to create searches based on fields derived from simple joins (1:1/N:1) or from 1:N relation, you have to change the setting of the method used (from WMS to QGIS API). See dedicated paragraph.**

Every search widget will be saved by referring to the layer identifiers (for example the DB parameters: IP, DB name, schema, layer name).

This aspect allows, once a search widget for a layer has been created, to have it available on all the projects in which the layer is present, without having to rebuild the widget from scratch each time.

In the list of layers present within the project, identify the layer on which to create and associate the search widget



Label 👫 Name	.↓† Type .↓† WMSEx	ternal WFS Actions	No 11 legen	Download Download	d Download Download
Buildings buildings	/	•	% ≜ ₹ \$		
Add new widget					
Actions		Name		Туре	Linked
/ =		Like test		search	
/ *		Type and volume		search	
/ =		Different from		search	
/ =		Double AND		search	

By clicking on the icon, the list of already active (or activatable) widgets associated with the layer will be shown.

These widgets can be modified, deleted or disconnected using the appropriate icons.

ATTENTION: deleting a search will delete it from all projects in which that search is active.

To deactivate a search from a project, simply disconnect it using the check-box on the right.

To create a new search, click on the link New widget.

In the pop-up that appears, the **Search type** have to be chosen.

Form title	×
Type*	Name*
~	
Search	
Law	🗙 Close 🗸 Ok

In the related form we can define:

- Form Title
 - Type: "Search"
 - Name: name that G3W-SUITE will use to internally register the search widget.
- · General configuration of research and results
 - Search title: title that will become available in the 'Research' panel of the WebGis interface
- Search fields settings
 - Field: field on which to carry out the research
 - Widget: method of entering the value to be searched
 - * InputBox: manual compilation
 - * SelectBox: values shown via drop-down menu
 - * AutoCompleteBox: values shown through auto-complete mode
 - * DateTimeBox: widget to be used exclusively for date type fields. On the client, the user will define the date/time to search through the calendar/clock widget.
 - Alias: alias assigned to the field that will appear in the search form
 - Description: description assigned to the field
 - Comparison operator: comparison operator (=, <,>,> <,> =, <=, LIKE, ILIKE) through which the search query will be carried out.
 - **Dependency:** this parameter (optional) allows, only in the case of **SelectBox** or **AutoCompleteBox** widgets, to show the list of values of a field filtered according to the value defined for the previous fields.

Now it is possible to define the dependence more or less strong (strictly).

In case of **strictly dependence**, the values of the dependent fields will be loaded **only after** the choice of the value of the field on which the dependency depends.

Otherwise it will be possible to define the values of the individual fields freely and **without a specific order**. The values available for the other fields will in any case depend on the choice made.

ipe		Name*		
Search		∽ Type a	nd year	
General configura	ition for se	earch widget and re	esults	
Search title				
Type and year				
Client search title iden	tification			
Search field settir	ngs			
ield		Widget	Alias	Description
type	~	SelectBox ~	Туре	
			Alias field name for client search	
			input	
			mpuc	
omparison operator			mput	
comparison operator = (equal)	~		mpor	
Comparison operator = (equal) Dependency	~		mput	
Comparison operator = (equal) Dependency		AND	mpor	
Comparison operator = (equal) Dependency Search field setti	~ ~	AND		
Comparison operator = (equal) Dependency Search field settin	v v	AND	wpo. v	Description
Comparison operator = (equal) Dependency Search field settin Field year	v v ngs v	AND Widget SelectBax v	mpor v Alias Vear	Description
Comparison operator = (equal) Dependency Search field settli Field year	∼ ∽ ngs	AND Widget SelectBax v	Alias Year Alias field name for client search injust	Description
Comparison operator = (equal) Dependency Search field settli Field year Comparison operator	~ ~	AND Widget SelectBox v	Alias Year Alias field name for client search Input	Description
Comparison operator = (equal) Pependency Search field settin Field year = (equal)	ngs	AND Widget SelectBox ¥	Allas Year Allas field name for client search input	Description
Comparison operator = (equal) Dependency Search field settin Field year = (equal) Dependency E (equal)	ngs	AND Widget SelectBox ~	Mias Year Alias field name for client search input	Description

Tip In the event that, at QGIS project level, the following editing widgets are associated with a field:

- Value relations
- Value maps
- Relationship reference

The values shown in the search tool will be those defined on the basis of the tables related via widegt.

Warning: in the case of fields with more than 100 unique values, the WMS service does not allow to obtain the complete list of values. In this case it is recommended not to use the SelectBox method

Alternatively, you can use the QGIS API as a search method to overcome this limitation. See dedicated paragraph.



The button allows you to add additional fields for the construction of the search query currently manageable through **AND/OR operators**.

The example below shows the compilation of the form for creating a search widget dedicated to a cadastral cartography layer.

pe*		Name*		
Search		✓ Type an	id year	
General configura	tion for se	earch widget and re	sults	
earch title				
Type and year				
lient search title iden	tification			
iearch field settir	ngs			
ield		Widget	Alias	Description
type	~	SelectBox 🗸	Туре	
			Alias field name for client search	
			input	
Comparison operator			Input	
Comparison operator = (equal)	•		input	
Comparison operator = (equal) Dependency	~		input	
Comparison operator = (equal) Dependency 		AND	input v	
Comparison operator = (equal) Dependency Search field settin	v	AND	input v	
Comparison operator = (equal) Dependency Search field settin Field	v v	AND	input v	Description
Comparison operator = (equal) Dependency Search field settin Field year	v v ngs	AND Widget SelectBox v	input v	Description
Comparison operator = (equal) Dependency Search field settle Field year	v v ngs	AND Widget SelectBox v	Allas Vear Allas field name for client search inout	Description
Comparison operator = (equal) Dependency Search field settli Field year Comparison operator	~ ~	AND Widget SelectBox V	Input Allas Vear Allas field name for client search input	Description
Comparison operator = (equal) Dependency Search field settli Field year Comparison operator = (equal)	ngs	AND Widget SelectBox v	Input	Description
Comparison operator = (equal) Dependency Search field settli Field year Comparison operator = (equal) Dependency	v v ngs v	AND Widget SelectBox ~	Input	Description

Once the form has been filled in, click on the OK button to save the settings.

Once the settings are saved, the created widget will appear in the list of Widgets associated with the layer.

The widget will already be connected and therefore available in the WebGis interface.



IMPORTANT: the created search widget will now be available (disconnected) for all projects in which the layer with which it has been associated will be present.

This will allow you not to have to recreate the widget several times and to decide in which projects to activate the search and in which not.

Multiple layers search

The **Other searching layers** option allows you to extend the search carried out to other layers.

If the additional layers have homologous fields (same name and type) the search will be extended to them.

The results will be differentiated according to the corresponding layer.

Especially useful in the case of multi geometric layers.

Other searching layers

× roads × Work areas

Select one or more additional layers to search on

Search based on 1:N relation data

The option allows you to create a search based on the fields of a table (child in a 1:N relation) and obtain results relating to the parent layer of the relation.

N.B. to create searches based on fields derived from simple joins (1: 1 / N: 1) or from 1: N relation, you have to change the setting of the method used (from WMS to QGIS API). See dedicated paragraph.

The **Relations** option allows you to to define the relationship to be used (if present) to identify the parent layer whose results will be shown.

Relations

Maintenance works		•

This layer is a child in a relation, if you want to excute the search on father layer of relation, select the relative relation

11.8.8 Manage layer styles

If multi styles have been associated with the same layer in the QGIS project, they will be exposed.

It will be possible to associate new layers by loading related QML files and set the style to be used as default.

Label	↓≟ Name ↓î	Type $\downarrow\uparrow$ WMS External $\downarrow\uparrow$ WFS $\downarrow\uparrow$	Actions	lt i	No legend ↓↑	Download as shp 1	Downloa as gpkg	ıd ↓↑	Download as xls	1t	Download as csv	1t	Download as gpx	11
Buildin	gs buildings	1	■ Ø % ▲ T ¢ ✓											
	Create New Style From QML													
	Actions	Name					Current							
	i /	Graduated style					0							
	i /	Year style					0							

11.9 Multilinguage

By default the suite manages four languages:

- English
- French
- Italian
- Finnish
- Swedish
- Romanian

Other languages can be added.

11.9.1 Map client

On the top bar you can choose, through a drop-down menu, the language of the entire client interface.



11.9.2 Administration

Also for the Administration panel, through the same drop-down menu, it is possible to define the language of the entire interface of the console.

	A admin01	Italiano	
Someone	- Summer	Tratiano	

11.9.3 Front end

Fixed front end content is already available in the four basic languages.

Variable contents, i.e. user-definable contents, are instead translated:

- Sessions Home, About, Maps and Login: content that can be defined and translated in the Edit General Data session of the Control Panel Administration
- Sessions MacroGroups Cartogarfici, Groups Cartogarfici and WebGis Services: contents definable and translatable in the form defining these elements, limited to the items:
 - Public Title
 - Description

To carry out the translation of these contents, proceed as follows:

- access to the form for creating the element (MacroGroup, Group or WebGis Service)
- define one of the available languages from the drop-down menu at the top right
- fill in the form in the chosen language
- save the settings

93W SUITE	=	🕷 Frontend 🔺 admin01 🔰 📢
i MENU	Gruppo Dipartimento Ambiente	Bashboard → Gruppi cartografici → Agg, grup, Inglese → tre
Gruppi cartografici Y	Add project	
+ Aggiungi gruppo G Lista gruppi	Corrente 3 Progetti	
😧 Macro Gruppi cartografici 🔇	Dati generali	ACL Utenti –
FACL	Nome" dip_ambiente	
	Titolo*	Set Editor Level 1 owner Editor 2 user
	spatial Gala Descrizione	
		Utenti Viewers × (AnonymousUser)
	Maps of environmental interest	Gruppi utenti editor
		Gruppi utenti viewer
		* gruppo_ambiente_viewer * g_viewer_ambiente_servizio1
	e	Propaga i permessi dei NUOVI utenti viewer e gruppi di utenti viewer aggiunti
		Auropa c

Then:

- access the form again in modification
- change the language
- fill in the translatable content in the new language
- save the new settings

Titles and Descriptions of the various elements in the defined languages will be available on the front.

CHAPTER

TWELVE

G3W-CLIENT: THE CARTOGRAPHIC CLIENT

12.1 Generic aspects

The application has a responsive interface consisting of expandable and reducible sessions.

The color of the interface depends on the type of user logged in.



The header contains the following elements:

- Logo, title and subtitle, deriving from:
 - main title (set at General Data level) or MacroGroup name, according to the settings
 - Cartographic Group name

- WebGis service title
- **Change map:** which allows you to switch from one WebGis service to another (located within the same Cartographic Group) while maintaining extension and display scale
- User ID: if you have logged in to the system
- Credits
- Home: to access the FrontEnd
- Language: the choice of language is reflected in the individual menus of the map client and on the contents of the access portal. The languages available are those activated by the Administration.

SUTE G3W-SUITE Demo ∓ Change Map ≜admin01. € Credits English

The **Tools panel** is located on the left and containing the following objects:

- Metadata: any content defined in the GetCapabilities of the QGIS Project
- Print: printing tool based on the layouts defined on the QGIS project
- Search: with the search tools defined in the Administration session, as well as a free Query Builder like the one present in QGIS
- Charts: visualization of any graphs created on QGIS with the DataPlotly plugin
- **Spatial Bookmarks:** tool for using the Spatial Bookmarks associated with the QGIS project and allowing the user to create new ones for his exclusive use.
- **Tools:** session that collects the various tools that may be activated on the WebGis service (including editing tools)
- WMS: session to add custom WMS services to the map
- Map: containing:
 - Layers: structured list of layers, defined on the QGIS project
 - Base: choice of the base map from those defined at the creation level of the Thematic Group
 - Legend: graphic legend of the various layers



In the event that **Themes** (Views) are defined in the QGIS project, a specific choice menu will be available in the Layers session of the TOC.

The choice of a Theme will determine the **automatic activation of the layers and related styles**, defined in the Theme itself.



12.2 Navigation and interaction with the map

12.2.1 Map area

At the base of the map area there is an information bar showing:

- display scale
- **mouse coordinates**: coordinates can be shown in project projection system and in WGS84 LatLong (ESPG: 4326)
- project projection system
- icon to copy the URL with the references to the extension currently displayed

1:2768 🔹 👻	X: 1681114.8711, Y: 4851262.1546	[EPSG:3003]	S
------------	----------------------------------	-------------	---

12.2.2 Map controls

The icons and description of the functions of the various MapControls activated at the thematic group level are shown below.



zoomtoextent: zoom to the initial extension



zoom: zoom in and zoom out



zoombox: zoom tool based on drawing a rectangle



Zoom last/next: undo/redo tools to navigate previous and post visualization areas (icons in the down-left corner)



query: puntual query of geographical layers



querybbox: query via bounding box - **N.B.** for the layers to be queried according to this method it is necessary that they are published as WFS services on the QGIS project



querybypolygon: it will be possible to automatically query the features of one or more layers that fall within a polygonal element of a guide layer. (Eg what's inside a cadastral parcel?). - **N.B.** the questionable layers must be published as WFS services on the QGIS project

images/manual/querybydraw.png

querybydraw: query based on an irregularly shaped polygon drawn by the user - N.B. for the layers to be queried according to this method it is necessary that they are published as WFS services on the QGIS project



geolocation: geolocation tool (useful for consultation from tablet)

• **geocoding:** search tools for addresses and toponyms based on OSM or Bing, based on the providers activated at the administration level



streetview: Google StreetView on your map
- in the presence of GoogleMaps API Key, StreetView it is integrated on the client and synchronized with the position and direction of the icon on the map
- in the absence of GoogleMaps API Key, StreetView it will open on a new browse tab without the aspects of synchronization with the map



length: linear measuring instrument



area: tool for measuring surfaces



addlayers: tool for temporarily uploading GML, GeoJson, KML, GPX, SHP (zipped) and CSV with coordinate to WebGis. These layers will remain until the end of the work session



snapshot: tool for taking snapshots of the map area



GeoSnapshot: tool to export a GeoTIFF of the map area

Query type

It should be noted that the query function acts, by default, with the coring method, providing information relating to all the layers underlying the point where you click with the mouse or draw a box.

To query a single layer, it must be previously selected at the TOC level.

Remember that query modes based on querybbox, querybypolygon and querybydraw require the publication of all the layers involved as WFS services at the QGIS project level.

The result of these three types of queries can be based on the geometric operations intersection and containment.

The choice made via the drop-down menu allows you to move from one result to another dynamically.



The querybypoligon tupe works also on the polygon layers added using the AddLayer tool

NB: it will be possible to zoom on the feature associated with the individual results only if the option **Add geometry** to object response has been activated at the QGIS project level (**Project** \rightarrow **Properties, QGIS Server session**).

12.2.3 Map query

In the QGIS project (Vector properties \rightarrow Attributes Form), you can create custom attribute forms (tabs, groups ...)

Upon querying a geometry, the form structure will be replicated at the client level.

esults				
Buildings (1)			-
		fid	name	address
9 क़ ॼ ॾ	880	4	Pink buil	Via Giova
General Ir	nfo	Techn	ical data	
Identificat	ion	Docum	ents	
fid	4	nhoto		1
name	Pink building	photo		\$16g
address	Via Giovanni Lampredi	form	Оре	•
type	Residential	link	Оре	•

Any links to photos will determine the display of a clickable preview, any links to links or other multimedia content will determine the display of the Open button that will allow consultation of the link.

For further information on this point, see the dedicated paragraph.

Single result

In case the query provides one single result, the attributes will be displayed according to the form defined in the QGIS project or as a column list



The bar above the query results shows the following icons:

• Zoom to feature: if the function is activated on the Properties of the QGIS project

- Show relations (1: N): if present on the QGIS project
- Show relation charts: display of plots related to 1: N related data. Only if 1: N relationships are associated with the interrogated layer and plots have been activated on the referencing tables.
- Print Atlas: prints the reports (atlas) (if set on QGIS project) related to the queried feature
- Download single results (Shapefile, GPK, GPX, CSV, XLS): if activated in the administration session
- **Remove feature from result:** remove the feature to the current list of results (useful to choose manually the list of objects to select/download)
- Add/Remove selection: add/remove the features to the current selection
- Copy map URL pointing to the geometry : to create a parameterized URL that points to this features
- Editing: to start editing directly on this feature

Multiple result

In case the query provides more results these will be listed as a list with the possibility to expand the detailed information.

Results Type and	++ ÷ ×		
buildings (3)			9 🖶 🕹 🖬 🎱 –
9 ♣ 🖶 ≛ 🖬 🤅	001		
ID	Name	Description	+
3	Garibaldi Palace	2023-05-12T09:5	
9 ♣ 🖶 ≛ 🖬 🤅	81		
ID	Name	Description	+
6	Cavour Palace	2023-05-12T09:5	
◎ ♣ 🖶 ≛ 🗖 🤅	81		
ID	Name	Description	+
12	White house	2023-05-12T09:5	



A series of icons, relating to the list of resulting features, will allow you to:

- Zoom to features result extent: if the function is activated on the Properties of the QGIS project
- Print Atlas: prints the reports (atlas) (if set on QGIS project) related to all the features result
- Download all the features results (Shapefile, GPK, GPX, CSV, XLS): if activated in the administration session
- Add feature on result: add features (clicking on the map) to the current list of results (useful to choose manually the list of objects to select/download)

• Add/Remove selection: add/remove the list of features result to the current selection

12.2.4 Display of 1:n relation data

In the event that, at the QGIS project level, **one or more type 1:n relations** have been associated with a layer, the icon **View Relationships** will be shown in the attribute form.

By clicking on the icon you will access the **list of 1:N relations** present and, from these, the list of child records associated with the individual relationships.

In the case of a simple 1:1 or N:1 joins, the joined records will be displayed directly in the main form.

In the new frame, a filter, applied generically to the contents of all fields, will allow you to filter the list of child records.

The icon to the left of each record allows you to switch from the classic table view to the one based on any form defined on the QGIS project

In the case of **links to multimedia contents**, the previews of the images and/or the **Open button** will be displayed for consultation of different types of content.

In case of **active plots** on the related table, these will be displayed through **Show charts** at the top right.



12.2.5 Parameterized URLs

It is possible to create parameterized URLs for direct zooming to: geographical extension single feature by FID single/list features by value of a field

Here the URL parameters available:

- map_extent (Zoom to map extent)
 - Ex: <url_project>?map_extent=Xmin, Ymin, Xmax, Ymax
- zoom_to_fid (Zoom to a specific feature by FID)
 - Ex: <url_project>?zoom_to_fid=<layer_id>|<fid value>
- ztf (Zoom to features defined on the basis of attribute values)

- Ex: <url_project>?ztf=<layer_id or layer name>:<field name>=<field value>

If Views (Themes) are set up in the QGIS project, it will also be possible to parameterize them in the webgis URL:

• Ex: <url>?map_theme=<theme_name>

12.3 Tools panel

12.3.1 Metadata

The metadata reported in this session derive from those set at the QGIS project level.

This content is divided into three sessions: General, Space Info and Layers.

- General: reports the metadata defined on the QGIS project in the item: Project → Properties (QGIS Server session, Service Capabilities) In case of login as anonymous user the URL of the WMS service is shown.
- Spatial: reports the EPSG code of the projection system associated with the QGIS project and the Bounding-Box relating to the initial publication extension, defined in the item: Project → Properties (QGIS Server session, WMS Capabilities, Advertised extent)
- Layers: reports simple metadata associated with the individual layers.

Metadata Building management Demo			
GENERAL		SPATIAL	
TITLE	Public building manage	ment SpatiaLite	
NAME	WMS		
ABASTRACT	Manage public builds ar form and editing widget	nd registering individual maintenance interventions. I t defined at the QGIS project level.	Layer properties, 1:N relation, charts, print layouts, query
KEYWORDS	qgis, webgis, g3wsuite		
FEES	no conditions apply		
ACCESS CONSTRAINT	None		
CONTACTS	Refereces	Person Leonardo Lami Organization Gis3W snc Position author	
	Phone	+39 393 8534336	
	🔤 Email	info@gis3w.it	

12.3.2 Charts

View graphs created using QGIS DataPlotly and activated at the admin session level.

Check the plots in the list and consult them on the rigth panel.



The graphs are filterable based on the:

- Metatures visible on the map
- **T** filter based on the selected features

These filters are also reflected on the plots associated to the related data (in 1:N mode) based on the visible and/or selected parent features.

The **filter based on the map content** can be activated globally on all plots (icon at the top of the panel dedicated to charts) or on only some specific plots (icon placed at the level of the individual plots).

The plots will automatically update after pan and zoom operations on the map

If activated, the **filter based on the selected features** is automatically activated on all related plots (associated with the same layer and with the 1:N relationed tables)

Appropriate messages at the single plots level will indicate the activation of these filters.

Charts based on 1:N data relation (child layer)

If the **chart is linked to a child layer in a 1:N relation**, it can also be displayed at the information level of the individual parent features



12.3.3 Print

Printing tool based on layouts defined on QGIS project.

The tool allows you to choose:

- Template: print layout among those associated with the published QGIS project
- Scale: print scale
- DPI: print resolution
- **Rotation:** rotation angle
- Format: print to PDF or JPEG
- **Custom title:** using the **ItemIDs** at the print layout level of the QGIS project it is possible to insert one or more labels with **customized content in the print** from WebGis

On the map, a light rectangular area will allow you to define the print area.

🖶 Print
i The layers shown in the print could be those defined on the project and not those displayed on the map
Template
A4 horizontal 🗸 🗸
Scale
1:5.000 ~
dpi
150 ~
Rotation
0
Format
PDF v
Labels
Custom label
Define the content
Create Print

If an **Atlas type print layout** is associated in the QGIS project, the layout reference will be available. The cards to be printed are defined by referring to the atlas identifier defined in the print layout.



12.3.4 WMS

Through this tool the user can add custom WMS layers to the WebGis service.

The user can add one or more WMS service by defining:

- custom title
- WMS URL

S www.s
Name
RT - Administrative
URL
r/com.rt.wms.RTmap/wms?map=wmsambamm

After that, using the + key it is possible to view the list of maps associated with the service, choose which one to load by defining:

- the position (top or buttom) with respect to the other layers of the project
- the layer to load
- the projection system to be associated
- a custom name



When the first custom WMS is added, a new tab (WMS) appears in the TOC; here you can switch on/off or delete the individual added WMS layers.



The added WMS layer cannot not be queried.

The list of WMS services and the specific WMS layers added will remain available to the user until the browser cache is cleared.

12.3.5 Search and Query Builder

A classic Query Builder is present at the Search menu level. Through this tool it is possible to:

- · carry out alphanumeric searches on geometric layers
- save the query to reuse it until the end of the work session
- edit a previously saved query

The saved query will be available until the browser cache is cleared

NB: fields not exposed as QGIS project-level WMS are not available for query building.

Query Bui	lder		×					
Buildings			×					
FIELDS								
date_exits			^					
fire_system								
date_fire								
type								
VALUES								
Residential								
Commercia	L I							
Administrat	ive							
MAN	MANUAL ALL							
OPERATORS								
=	1=							
80	~	IN	NOT IN					
LIKE	ILIKE	AND	OR					
EXPRESSION								
EXPRESSION "type" = 'Commercial'								
TEST	CLEAR	RUN	SAVE					

The Search menu contains the list of search tools defined through the Administration panel and custom searches created with the Query Builder.

Q Search
O Like test
O Type and volume
O Different from
O Double AND
O Simple OR
O Data
O Type and year
O AND and OR
Y Query builder search

You choose the search you are interested in, fill in the required fields and click on the Search button.

The **panel with the list of results** will open on the right side of the client, for each result the first three fields of the associated table will be displayed.

By positioning on the individual results, the corresponding features will be highlighted on the map; clicking on the individual results you can consult all the attributes.

Zoom to features and download icons are available for results (single or cumulative)



12.3.6 Map

This session has three tabs:

- Layers: structured list of layers, defined on the QGIS project
- Base: choice of the base map from those defined at the Cartographic Group creation level
- Legend: graphic legend

Layers

This tab shows the layers prepared on QGIS projects with the same organization the groups and subgroups.

If the **Show features count** function is activated in the project, the layer will show the number of total features and based on the subdivision linked to the symbology.

In case of multi-style associated with the layer, the number of geometries reported will vary following the passage from one style to another.



In the list of layers, right click on the name of the single layer shows the following items:

- Name and kind of geometry of the layer
- Metadata: descriptive information inherited from what has been defined, at QGIS project level, in the 'Abstract' form of the 'QGIS Server' session of the 'Layer Properties'
- Styles: to choose the style to be applied to the layer, in the case of multi-style layers

- Abstract: a text (also html) defined in the Layer Properties, Metadata session, Identification tab, Abstract form.
- Zoom to layer: to zoom in on the extension of the layer
- Open attribute table: to consult the associated attribute table
- Download shapefile: to download the layer as a shapefile; function activatable from the administration panel
- **Download GEOTIFF:** to download a raster in GeoTiff format, full layer or clipped to the extent of the canvas; function activatable from the administration panel
- **Download GeoPackage:** to download the layer as a GeoPackage; function activatable from the administration panel
- Download CSV: to download the layer as a CSV; function activatable from the administration panel
- Download XLS: to download the layer as a XLS; function activatable from the administration panel
- WMS/WFS URL: URL of the WMS/WFS service relative to the project or URL of the external WMS



Double clicking on the layer or Layer Group zooms to the extent of the layer or Group content.

It is possible to hide, automatically, layers from the TOC when they have no records.

Useful when using filters on layers or geographic views.

Attribute table

The attribute table (resizable) is equipped with **paging function, highlight function and zooming** to the associated features.

In the case of links to **multimedia content**, the previews of the images and/or the **Open** button will be displayed for consultation of different types of content.

The window is resizable.

Buildi	igs														×
Show 10	~ ወ													Search	
	fid	name	address	year	phote	link	form	high	volume surface	architectural_barriers	date_barriers	safety_exits	date_exits	fire_system	date_fir
	fid 🔺	name 🕴	address	year	🕴 photo 🕴	link 🕴 🕴	form \$	high 🕴	volume 🕴 surface	architectural_barriers	date_barriers	safety_exits	date_exits 0	fire_system	date_fit
	1	Purple building	Piazza Pietro Leopoldo	2019	-	Open	Open	11	200	Cheked	2018-08-06	Checked	2018-08-07	Checked	2018-(
	2	Green building	Via Alfredo Oriani gia' Via Vecchia	2019	R.	Open	Open	18	120	Not checked	2018-06-04	Checked	2018-08-07	Not checked	2018-4
	3	Orange building	Piazza Pietro Leopoldo	2020	2.	Open	Open	16	150	Not checked	2018-08-29	Checked	2018-08-29	Checked	2018-1
	4	Pink building	Via Giovanni Lampredi	2020	- 44.1	Open	Open	11	150	Cheked	2018-10-03	Checked	2019-10-15	Checked	2018-:
<					-	_	_						_		, ×
Showing	l to 10 of 1	3 entries											Previou	JS 1 2	Next

A **generic filter**, positioned at the top right, is applied generically to the contents of all the fields, and it will allow you to filter the list of displayed records.

Filters based on the contents of the individual fields are available at the top of each column.

The **Show features visible on the map** icon allows you to filter the records of the table according to the features visible in the map.

It is possible to select the features of the individual layers and apply filters that will affect:

- on the map content
- on the attribute table content
- on the contents of the plots
- on print contents
- on the editable geometries

The selection of features can be made:

- at the attribute table level (through the checkboxes on the left of each records)
- on the results of a query (add / remove from current selection)
- on the results of a query (add / remove from current selection)

At the same time, additional icons appear:

- on the layer attribute table
- to the right of the layer on the TOC
- at the level of the relevant plots

Aggiungi immagine: g3wclient_selection.png The icons in the attribute table allow you to:

- Clear selection
- Invert selection
- • Add/Remove filter

The icons to the right of the layer on the TOC allow you to:

- Clear selection
- Add/Remove filter

🛛 Buildings 🛛 🔗 🝸

When one or more features are selected, they appear highlighted in red on the map. Activation of the filter is reflected:

- on the map content
- on the attribute table content
- on the data displayed by plots
- on the print contents (only with QGIS 3.18)

Filter users based

On the client you can select (highlight) and filter a subset of vector layer geometries.

It is possible to activate a filter on a layer starting from:

- query results
- search results
- attribute table management

To be filtered, the geometries object of the filter must first be selected.

Following activation of the filter, a logged in user (not AnonymosUser) will be able to save this filter to be recalled in subsequent work sessions.

Saving the filter occurs via the dedicated icon present at layer level in the legend and in the results form.

▼							
▼ 🗹 Official demo							
🔻 🗹 Geographical group							
🔻 🗹 buildings [13] 🛛 💉 🍸 🕞							
Administrative [5] Commercial [3] C Residential [5]							
roads							

The saved filters can be recovered via the dedicated menu that can be viewed by right-clicking on the name of the layer



The presence of an active filter on the layer is highlighted by the red icon next to the layer name.

To deactivate an active filter, simply click on the icon itself.



We remind you that activating a filter affects:

- geometries visible on the map
- records visible on attribute table
- · editable geometries
- features underlying the graphs
- print contenent

Base layer

The list shows the active base layers at the cartographic group level.

If the user has created base layers starting from cached layers, these may also be present.

Legend

If at the publication level of the QGIS project, the **Legend position** option i setted as TOC, this panel will be not present and the legend will be rendered inside layers TOC.

If the option is activated on the QGIS project, the legend is filtered on the map content.

12.4 Time series

NB: the Time Series function is only available with a QGIS Server version >= 3.26

This version of G3W-SUITE manages the temporal aspects for both vector and raster layers but with limitations:

- vector layers: limited to the Single field with Date/Time configuration
- raster layers: Mesh layer
- WMS-T

It is possible to create animations based on multiple temporal layers both raster and vector.

If in the QGIS project a temporal vector/raster layer on which the **Dynamic temporal control** property has been activated is present, the client will show an additional panel called **Time series**.

This panel will allow you to:

- · define the start/end date of the time series
- define the step of the animation
- start and manage the temporal animation

() Time Series	
Layer	
ASAM_events	٣
Start Date	
2000-01-02	
End Date	
2018-01-01	#
Step [Days]	
1	\bigcirc
Steps	
-	
н н – 💶 🕨 н	ж

The modification of the start date of the series will determine the updating of the map with the visualization of the layer in coherence with the chosen date.

Pay attention: to use the Time series function for raster data, it must also be activated at the level of the G3W-ADMIN layer properties.

Data 🖬 Structure		
Show 10 v entries		Search:
Label 🗄 Name 🕂 Type 🎝 WMS External 🎝	WFS 👫 Actions	Notzhow attributes No Download Download Download Download Download 1 table 11 legend 1 aszhgigeotiff 1 azgkg 1 asis 1 ascv 1 azgx
climatology- air_temperature_monthly- pr-monthly- mean ∞ mean	۲	• •

CHAPTER

THIRTEEN

EDITING ON LINE

13.1 Activation and configuration

13.1.1 Introduction and main features

The editing settings are defined partly at the QGIS project level (editing form structure, widgets associated with individual attributes, 1:n and, in part, N:M relations) and partly at the Administration level (users with editing power, activation scale, alpha and geo constraints).

Thanks to the integration with the APIs of QGIS it is now possible to manage the main formats (geographically and not) supported by QGIS Server:

- reading and editing mode
 - PostGreSQL/PostGis
 - SQLite/SpatiaLite
 - Oracle Spatial
 - GeoPackage
 - ShapeFile
- reading mode
 - SQL Server
 - Virtual layer

Pay attention! An important note in relation to the formats supported in editing: please remember that only data on PostGreSQL/PostGis and Oracle Satial support multi-user editing.

Multi-user editing on formats such as Shapefile, but also GeoPackage and SpatiaLite, can lead to data corruption.

13.1.2 1:N and N:M relational editing

The editing function manages both direct editing on geometric and alphanumeric layers, and editing on layers in a 1:N or N:M relations, also both geometric and alphanumeric.

Attention: the management of the editing of the N: M relations is limited to the management of the 1:N relationship between the parent layer and the intermediate table.

This means that currently it is not possible to create new records in table M but only:

- modify the current relations present
- · create new relations between new elements of layer N and pre-existing records of layer M

The editing settings are defined partly at the QGIS project level (editing form structure, widgets associated with individual attributes, 1:n and N:M relations) and partly at the Administration level (users with editing power, activation scale, alpha and geo constraints).

13.1.3 Multi-user editing

G3W-SUITE manages multi-user editing through a feature lock system.

It's strongly recommended to allow multi-user editing only in the case of layers on the GeoDatabase and not on physical files.

When an enabled user activates the editing function at the map client level, the **features visible on the map at that time will be blocked**, in relation to the editing aspect, **for all the other enabled users** who will still be able to edit features present outside this geographical extension.

In case of features of a layer locked by other users, the user will receive a warning message when starting the editing.

This block will be deactivated when the user exits the editing mode.

13.1.4 QGIS project settings

Definition of editing widgets associated with individual attributes

In the QGIS project, for each layer it is possible to define the structure of the attribute display module.

The same structure will be used in the cartographic client when editing attributes.

The definition of the form structure can be managed, on QGIS, from the **Properties of the vector**, in the **Attributes Form section**.



Conditionals forms based on QGIS expressions

Conditional forms based on QGIS expressions are supported and implemented for online editing/consulting.

It is therefore possible to define the visibility of a forms (form or group) and of the fields it contains, on the basis of the values defined on further fields when filling in the attributes.

Drill-down (cascading) forms

Drill-down (cascading) forms based on QGIS expressions are supported and implemented for online editing.

The functionality can be used to implement "drill-down" within editing forms, where the values available in one field depend on the values of other fields.

This function will be reflected in the consultation side.

Definition of editing widgets associated with individual attributes

At the QGIS project level (always from **Vector Properties**, **Attribute Form** section) it is possible to define an alias and an editing widget for each attribute.

The alias and editing widgets defined at the project level will be available during web editing with some limitations.

Below are the available widgets and any limitations:

- Relation reference: with some option limitation
- Checkbox
- Date/time: management limited to the date
- Attachment
- Range
- Text edit multiline and html included
- Unique values: this widget will be equipped with a pick layer tool at the cartographic client level
- Value map
- Value relations with QGIS expression-based filter management, the suite not support sort by value and allow multiple selections options

The expression-based filter can also be dependent on the values of other fields on the form and useful to create cascading drill down.

With regard to the **Attachment widget**, it is necessary to specify that the association of a multimedia file with a feature requires that this file is uploaded to a dedicated space (exposed on the web) on the server and that the association takes place via a URL that refers to that file.

This solution allows you to consult the associated attachments also from QGIS or from other GIS software.

Additional settings at single layer level

In the Attribute Form section of the Layer Properties it is also possible to define for every field:

- · enable/disable editing
- · mandatory and/or unique constraints
- range of acceptable values through the Range widget
- default values
- conditional forms

QGIS expressions and default values

All the QGIS expressions can be used as default values.

The default values defined for individual fields at the QGIS project level are inherited from the suite.

In this case, at the online edit level, the form relating to the field thus defined will be self-calculated and can be set not editable by the user.

The result of the expression can also be dependent on the values of other fields on the form.

Very useful in all cases where we want the values of a field to be calculated automatically through the potential of QGIS expressions.

The Apply the default value also to the update option is supported.

As in QGIS the default values are displayed in the form during editing and not only after saving.

Definition of 1:n relations

In the event that, at the QGIS project level, one or more 1: n type relationships have been associated with a layer (**Project menu** \rightarrow **Properties..., Relations section**), it will be possible to carry out relational editing also on the webgis platform.

Also for the tables related in 1:n mode it will be possible to define the **attribute form structure**, **aliases and editing widgets** in the QGIS project.

These configurations and tools will automatically available on the webgis platform.

Transaction Group

Use transaction group to edit, save or rollback multiple layers changes at once

When working with layers with the same source (es. layer from the same PostGreSQL database), activate the **Automatically create transaction groups where possible** option in **Project** \rightarrow **Properties...** \rightarrow **Data Sources** to sync their behavior (enter or exit the edit mode, save or rollback changes at the same time).

😣 🗊 Project Properti	es Data Sources				
Q → General → Metadata → CRS	 Automatically create trans Evaluate default values or Trust project when data so Layers Capabilities 	saction groups a provider side ource has no m	where possible	e	
💉 Default Styles	Layer	Identifiable	Read-only	Searchable	Required
Data Sources Data Sources Relations Variables Macros	 Anthropic elements Buildings join Maintenance Roads Work areas Base map CTR multiscale 	✓ □		> > >	
💽 QGIS Server	Toggle Selection		Show spatial l	ayers only	Cancel OK

13.1.5 Administration settings

Activation of on-line editing on a single layer

To activate the online editing functions, access the **Layer list** section of the project within the administration panel of G3W-ADMIN.

QGIS Project Layers			8	Dashboard > Car	tographic groups	Projects list G3W-SUITE Dem	D > Layer list QGIS pro	oject g3w-suite-demo
Project								
Public building management An example of cartographic managem To test the features and power of onli • user: viewer1 • pwd: G3wsuite123	Demo nenr rich in analytical functions, researches, graphs and much m ne editing, log in with the following credentials	ore.						
Show map Show detail Edit								
Data Structure								
Show 10 v entries						Sea	irch:	
Label	Name	lî Type lî WMS External l	WFS I Actions			Download	Not show attributes Iî table Iî	No legend ↓↑
buildings	buildings 👁	/		2 * 📕	₽.0 Çı ү 🔒	Download	•	
Buildings rating	buildings_rating 👁	1		8 🛋 📍	# # 🎾	▲ Download		•
Maintenance works	maintenance_works 👁	1		8 🔤 🕴	₿₿ 🎖	≛ Download		
roads	roads 👁		•	2 2 1	₽₽₽₽	Download		

Identify the layer on which you want to activate the editing function and click on the **Editing layer icon** located on the left

Attention: check that the layer format is among those supported by QGIS for the editing function

Clicking on the icon will open a modal window that will allow you to:

- define the editing activation scale (only for geometric tables)
- define the Viewer users (individuals or groups) enabled for online editing

For each user (single or group) it is possible to discriminate the editing powers:

- Add: add feature, copy feature, add part to multipart
- **Update geometry:** update vertex feature, move feature, add part to multipart, delete part from multipart, split features, dissolve features
- Update attributes: update feature attributes, update attributes of selected features
- Delete: delete features

I should be noted that:

- Viewers users (individuals or groups) available in the drop-down menu will be limited to those who have allowed access in consultation to the WebGis project
- Editor1 and Editor2 users, owners of the project, are enabled by default to the online editing function

Activation	layer_ed	iting		×
Check on uncl	heck to atti	ve/deactive editing layer o	apabilities:	
Scale				
2500				0
Scale after tha	at editing m	ode is active		
User adding o	data field			
user				*
Optional: sele Value stored in	ct layer fiel nto the field	d to store username that (d it will be so structured: [entered the data. Showed only username]	string field.
User editing	data field			
				Ŧ
Optional: sele Value stored in	ct layer fiel nto the field	d to store username that i d it will be so structured: [ipdated the data. Showed only isername]	y string field.
Select viewers	s with 'view	permission' on project th	at can edit layer:	
× (viewer)	L)			
Select user wi	ith viewer n	ole can do editing on laye		
User	Add	Update geometry	Update attributes	Delete
(viewer1)				
User viewer g	groups			
Select VIEWER	R groups ca	n do editing on layer		
			x C	lose 🗸 Ok

NB: In case a user belongs to a user group, the permissions set will be added together.

Ability to associate references to create/update G3W-SUITE users

Through these two optional settings it is possible to define two fields of the table of the layer being edited automatically filled in.

These two fields will contain references to G3W-SUITE users who creators or modifiers of the individual features edited.

All settings defined at the QGIS level for these fields (eg default values) will no longer be considered.

It is recommended that these fields be set as non-editable at the project level.

Activation of online editing on multiple layers at the same time

In the case of a project in which it is necessary to activate the online editing function on many layers, by defining the same options for each of them it is possible to use the Project layer action function.

Data 🔳	Structure				Editing		
				Project layers actions	s:		
Show 10	 entries 				Sea	urch:	
Label	↓ ≞ Name	WMS	al 💵 WFS 👫 Actions	11	Download capabilities	Not show attributes No table 🏦 leger	nd 💵
buildings	buildings 👁	/		≝ <mark>≜ 0,00</mark> ,117 ⊞	🕹 Download		

Activation layer_editing

×

A Important!
The following settings will be applied to all the layers indicated and will overwrite the settings set at the single layer level

Check on uncheck to attive/deactive editing layers capabilities:

	Active
~	ACTIVE

Layers*

 Buildings rating × Maintenance works × buildings
--

Select layers on which to activate editing

Layer	Add logging field		Update logging field	
Buildings rating		*		*
buildings	user	Ŧ		Ŧ
Maintenance works		Ŧ		*

Scale

|--|

Scale after that editing mode is active

Select viewers with 'view permission' on project that can edit layer:

Viewers

× (viewer)	1)			
Select user wi	ith viewer r	ole can do editing on layer		
User	Add	Update geometry	Update attributes	Delete
(viewer1)	 Image: A start of the start of			
User viewer (groups			
Select VIEWE	R groups ca	n do editing on layer		
			X C	lose 🗸 Ok

1:N relational editing

To allow editing on the related table in mode 1: n, the **editing function must also be activated** (always in the same way) **also for the related table** present in the project layers list.

Constraints setting

G3W-SUITE allows you to manage two types of constraints:

- alphanumeric (SQL) / QGIS expressions constraints
- geographic constraints

Both work in terms of visualization and/or editing

Alphanumeric (SQL) / QGIS expressions Constraints

Alphanumeric (SQL) / QGIS expression constraints allow you to define, for each published layer, the subset of features that can be viewed and/or edited by individual users and/or groups of users.

This setting is also available for the AnonymousUser user

To activate this type of constraint, you must click, always at the level of the list of project layers, on the **Alphanumeric** constraints list icon **T**.

Clicking on the icon will show the list of any existing alphanumeric constraints and the item + **New alphanumeric** constraint to create a new constraints.

🖉 % 🝸 🌞 🔼			et.	edifici	Public buildings
New alphanumeric constraints					
Actions	Name	Description		Subset rules count	Expression rules count

Clicking on the item **+ New constraint** will open a modal window which will allow you to define a name and a description for the new constraint.

In the form it is possible to specify whether this filter will act at the level:

- display only
- · editing only
- in both cases

New alphanumeric constraints	×
Set a name and a possible description for the alphanumeric constraint: Name	
Constaints name	
Description	
Free description	
✓ Active for visualization	
Active for editing	
🗙 Close 🗸	Ok

After clicking the OK button, the constraint will appear in the list and can be parameterized using two ways of defining the rules:



Provider's language / SQL dialect Rules

Clicking on the icon will open a modal window which, by pressing the green button allow you to **define, for each user and/or group of users, the rules of the constraints**.



×

The individual rules must be defined via the **Provider's language** or the **SQL dialect Rules** associated with the format of the geo-constraints layer (es. use standard SQL if your layer is a PostGis layer)

The single rules must refer to the layer's attributes and values.

The Save icon	س	will allow you to validate the rules, in order to ensure proper functioning of the constraints
itself.		

Constraint Rules based on provider's language / SQL dialect

Define, for each user and/or group of users, viewing/editing rules based on the language or SQL dialect of the associated provider.

Viewer		SQL		🖪 💼
(viewer1)	•	tipo = 'Administrative'		
User viewer group				
	•			
Viewer		SQL		🖹
	•	tipo = 'Commercial'	0	
User viewer group	_		G	
Viewer Group A	•			
		+ Add		
				🗙 Close

Once all the constraints have been entered and validated, click on the Close button to confirm the rules.

QGIS Expressions Rules

Clicking on the icon QGIS expression of the icon QGIS expr	ession rules E	will open a modal window wh here and/or group of users,	ich, by pressing the green buttor the rules of the constraints.
The individual rules must be defin ways in which to set these rules.	ned via QGIS exp	pression and this allows to have	e a great degree of freedom in the
See the paragraph dedicated to the	e functions availab	ble directly on the QGIS manual.	
The Save icon will allow itself.	you to validate t	the rules, in order to ensure prop	per functioning of the constraints
Constraint Rules based on QGIS E	Expression		×
Define, for each user and/or group of users	, viewing/editing rules	based on the QGIS expressions.	
Viewer	QGIS Expression		
(viewer1) •	area(buffer(\$geometry	y,100))	
User viewer group			
Viewer	QGIS Expression		P
	mean(\$area, "tipo")		6
User viewer group			
Viewer Group A			
		+ Add	
			X Close

Once all the constraints have been entered and validated, click on the Close button to confirm the rules.

In the dedicated panel it will be possible to check, modify and delete the defined rules.

New alphanumeric constraints						
Actions	Name	Description	For visualization	For editing	Subset rules count	Expression rules count
3 🚳	Building type view	Viewer3 vede solo Residential	•		1	0
3 🚓	Building type view/ edit	Viewer2 vede ed edita solo Commercial	•	0	1	0
🔒 S 🔒	Building type edit	Viewer 1 edita solo Administrative		0	1	0

Geo-constraints

The online editing function also allows you to manage geo-constraints that allow the user to view and/or edit features only if they intersect or are contained within specific features of a second polygonal layer.

This setting is also available for the AnonymousUser user

To activate a geographical constraint, you must click, always at the level of the list of project layers, on the Manage

Geo-Constraints icon

which will appear once the online editing function is activated.

Clicking on the icon will show the list of any existing constraints and the item + **New geo-constraint** to create a new geo-constraints.

3	% 🛢 ♦		4	Public buildings	
	New constraint				
	Actions	Layer constraint			Rules count
	&∎	Work Areas			2

Clicking on the item + New geo-constraint will open a modal window which will allow you to define the polygonal layer (among those present in the project) on which the constraint itself must be based.

In the form it is possible to specify whether this filter will act at the level:

- display only
- editing only
- in both cases

New constraint	×
Select the constraint layer, only Polygon or MultiPolygon geomentry: Constraint layer	
Work areas	-
Description	
Free description	
Active for visualization	
Active for editing	
X Close	✔ Ok

Once the layer has been defined, the constraint will appear in the list and can be parameterized using the Rules icon

&



The individual rules must be defined via the **Provider's language** or the **SQL dialect Rules** associated with the format of the geo-constraints layer (es. use standard SQL if your geo-constraint layer is a PostGis layer)

The single rules must refer to the layer's attributes and values.

The Save icon	Ы	will allow you to validate the rules, in order to ensure proper functioning of the constraints
itself.		

Viewer		QL	🖺 💼
(viewer2)	•	d=2	
User viewer group			
	-		
Viewer		OL	
(viewer1)	•	d=1	
User viewer group			
Viewer Group A	-		
		+ Add	

Once all the constraints have been entered and validated, click on the Close button to confirm the rules.

In the alphanumeric constraints list you can see a summary of the setted rules.

New geo constraint					
Actions	Layer constraint	Description	For visualization	For editing	Rules count
&	Work areas	Viewer3 vede solo Residential	0		1
&∎	Work areas	Viewer2 vede ed edita solo Commercial		0	1
&∎	Work areas	Viewer 1 edita solo Administrative	0	0	1

🕂 Add

it will allow

13.2 Online editing tools at cartographic client level

13.2.1 Geographic and alphanumeric editing

Once the online editing function has been activated and configured on one or more layers of a WebGis project, the Editing item, inside the Tools menu of the cartographic client, will be shown.

In the case of many editable layers, a useful filter allows you to view only the layers of interest in the list.

If the editing function is activated at the Admin level, it is also possible to start the online editing also through the **Editing icon** that appears at the level of the **search and query results form** of a vector layer.



By clicking on the **Data Layers** item, the side menu will show the editing tools for all the layers on which this function is activated.

The actual activation of the editing function for the individual layers will take place by clicking on the **Edit layer** icon.

Create and edit features

The tools available are the following:

Geometric layers



Update feature attribute: to modify the attribute values associated with an existing feature



Update feature vertex: to modify the shape of a geometry



Dissolve features: to dissolve two or more features

A help panel will describe the steps to take for copy, dissolve and split operations.

In case of interaction of the editing tools with overlapping geometries, an intermediate step will allow to select the effective geometry on which to operate.

Snap and other available function

Activating the Add features and Update feature vertex tools allows you to:

- activate the intralayer snap function
- activate the snap between layers, but only if both layers are in editing mode
- activate the interactive area and length measure function

Alphanumeric layer



respective editing widgets will be displayed as defined at the QGIS project level.

 Image: Sistema Informativo Territoriale Aree Naturali Protette Gestione pratiche di indemizzo per danni da fauna selvatica su colture, zootecnia e opere/strutture sul territorio
 # cambia Mappo
 # admin
 credits

 Editing Dati
 # Edita attributi danni da fauna su zootecnia
 # contenia
 Edita attributi danni da fauna su zootecnia

Editing Dati 🗙 🗏	Edita attributi danni da faun	fita attributi danni da fauna su zootecnia									
	Scheda anagrafica	I scheda attibuti zootecnia	II scheda attibuti zootecnia	N III scheda attibuti zootecnia							
Edit danni da fauna su zootecnia			1								
	Numero pratica *	122156543564erw	Anno della pratica *	2019							
Clicca su una feature per poterla modificare	Numero protocollo *	56456	Data protocollo *	2019-12-04							
Edit danni da fauna su opere/strutture		Compilatore (Cognome e Nome) ewnwenwerwe									
	Data segnalazione 2019-12-04 evento *	Data primo sopralluogo	1-27 👼	Stato della pratica * Annullata *							
Edit danni da fauna su colture	Area naturale protetta *	Antiche Città di Fregellae e Fabrateria Nova e del Lago di San Giovanni I 🔻	Ente gestore	Comando Unità per la Tutela Forestale, Ambientale e Agroalimentare (🔻							
	Dati del richiedente										
	Cognome *	rewrewrew	Nome *	WTWEREWFEWF							
	Denominazione ditta *	eewreewr	Indirizzo	ewrewrw							
		* ca	mpi richiesti								
		Satva	Cancella								

Any mandatory fields will be marked with an asterisk.

Any unfulfilled constraints will be highlighted with specific warning messages shown in red.

The changes made can be saved only after satisfying any constraints of mandatory and/or uniqueness.

For this reason the green button SAVE will be disabled until all constraints are met.

13.2.2 1:N and N:M related tables editing

G3W-SUITE allows for relational editing; for this to be possible it is necessary that:

- on the published QGIS project there are one or more geographic layers related (1:n or N:M) with one or more alphanumeric tables
- on the administration panel the editing function has been activated both on the parent layer and on the child layers
- the operator user is enabled for the editing function on these layers

The activation, at the cartographic client level, of the editing mode on the parent layer automatically determines the possibility of also managing the information on the related table.

Important: to be able to edit related data, the relations must be inserted in the form of the parent layer, defined using the Drag and Drop designer method in the Layer Properties.

After the editing has been activated on a record in the parent table, an editing icon (pen) will appear at the level of the relations references.

Editing attributes buildings					+ ;			
General info *			Technical data *					
Identification *			Documents					
ID*			Photo					
Name *	Pink building			casa-danzante-praga.jpg				
Address 🔂	Piazza Pietro Leopoldo	¥	Form					
Zone (QGIS expression)				building_detection_card.pdf	٥			
Туре*	Residential	×	Link	https://g3wsuite.it				
Subtype		×	User/Date last modification					
Documents to be attached	☑ 1							
Relations								
MAINTENANCE WORKS								
* Required fields Save Cancel								

Moving on the macro tab relating to one of the child layers, the list of records already associated with the edited feature will be displayed

Editing attribut	es buildings											+ #
Edit relation : MAI	NTENANCE WORK	s										
Search												@ +
Tools	Intervention ID 🔺	Building ID 🕴	Type of mainteinance φ	Date 🔶	Doc	uments	÷	Value 🕴	Outcome 🕴	Responsible 🕴	Cost 🕴	Validation 🔅
	6	4	Electrical system replacement	2020-02-04		building_detection_card_bUPcVab.pdf		29	good	Kurt Cobain	5000	1
	7	4	Restoration	2020-02-11		building_detection_card_R6hByU2.pdf		30	bad	Patti Smith	3500	0
	34	4	Electrical system replacement	2020-09-09		building_detection_card.pdf		10	good	Kurt Cobain	3000	1
	37	4	Restoration	2020-11-30		building_detection_card.pdf			medium	Axl Rose	2500	0
	41	4	Consolidation	2020-12-14		building_detection_card.pdf			good	Kurt Cobain	3000	0
Showing 1 to 5 of 5 entrie	5					Back					Previous	1 Next

Clicking on it the form switch in a session dedicated to the edit of the relational table where it will be possible: * **create** and add a new records related to the edited feature

- associate an existing records (linked to other features or orphan) to the edited feature
- modify the records currently associated with the edited feature

Creation of a new related child records

By clicking on the icon **Create and link a new relation** attribute form to insert a new record.

You can fill in the individual attributes and save the new record. The change must be validated by clicking on the Save button at the bottom of the form.

If the child layer is of the geometric type, it will be possible to add a new feature in two ways:

(located at the top right) it will be show the

- classic geometry editing
- copy and paste a feature from other layers (WFS included) present in the project and characterized by the same type of geometry

												+ #
Edit relation : M		c										
Search		-										@ +
Tools	Intervention ID 🔺	Building ID 🕴	Type of mainteinance	Date 🕴	Doe	cuments	¢	Value 🕴	Outcome 🕴	Responsible 🕴	Cost 🕴	Validation \$
	6	4	Electrical system replacement	2020-02-04		building_detection_card_bUPcVab.pdf		29	good	Kurt Cobain	5000	1
	7	4	Restoration	2020-02-11		building_detection_card_R6hByU2.pdf		30	bad	Patti Smith	3500	0
	34	4	Electrical system replacement	2020-09-09		building_detection_card.pdf		10	good	Kurt Cobain	3000	1
	37	4	Restoration	2020-11-30		building_detection_card.pdf			medium	Axl Rose	2500	0
	41	4	Consolidation	2020-12-14		building_detection_card.pdf			good	Kurt Cobain	3000	0
Showing 1 to 5 of 5 ent	les					Back					Previous	1 Next

To copy a geometry from another layer operate in this order:

- · select the layer from which to copy the geometry from the drop-down menu
- click on the Copy button on the right of the list
- click on the feature of the layer to copy from
- select the feature of interest by consulting its attributes and/or zooming in on it, only one feature per operation
- fill in the attribute form of the pasted feature, some fields may already be filled in if they are omonymus to those of the feature's origin layer

Association of an existing record

(located at the top right) you can associate a By clicking on the icon Join a relation to this feature record, already linked to other features or orphaned, to the edited feature.

In the new window displayed:

- the list of all orphaned or already associated records will be displayed;
- a generic filter will allow you to locate the record of interest;
- by clicking on the individual records these will be associated with the edited features and, possibly, dissociated from other features

Modification of an already associated record

A series of icons appear to the right of each record associated with the edited feature:

Unlink relation: to dissociate the record from the edited feature, the record will not be deleted but will become an orphan

• Delete feature: permanently delete the record

Update feature: modify the values associated with the attributes of this record; the change must be validated by clicking on the Save button at the bottom of the form.

Saving changes

Saving all the changes made in an editing session can be done in three ways:



- by clicking on the **diskette icon** placed at the top right. This icon is very useful in the case of complex projects with related data on various levels as it allows you to **save any changes made regardless of the form on which you are at the time of saving.** You will not be asked to confirm the save.
- by clicking on the **diskette icon** placed at the top left of the TOC. The icon will only be active once you exit the attribute editing form. The changes made will be saved and you can continue making new changes. You will not be asked to confirm the save.



• bexiting edit mode by clicking on the Edit layer icon

BExiting edit mode, a modal window will be displayed which will show the list of changes made and the request for confirmation or not of saving them.

Do you want to save the changes Public buildings?

The following list show all changes to commit.

Added show the number of features added

Modified and Deleted show the list of features id

- Added(n. features): 1
- Modified(id): [21]
- Deleted(id) : [99]

Relations

interventi_edifici20180829162722821

The following list show all changes to commit.

Added show the number of features added

Modified and Deleted show the list of features id

- Added(n. features): 0
- Modified(id) : [63]
- Deleted(id): [42]

Save Cancel

Remember that during the editing phase the **undo/redo icons** allow you to delete/restore the latest changes made.

×
FOURTEEN

INTRODUCTION

The tutorial is based on a QGIS project dedicated to the management of a layer representing a series of buildings located on the territory.

In addition to the geographical aspects, the project involves the management of numerous and diversified attributes and of the related maintenance interventions through a 1: n type relationship.

Through the tutorials it will be possible to:

- customize the various graphic-functional aspects of the basic project
- publish the project as a WebGis service
- create personalized searches
- add plots made with DataPlotly QGIS plugin
- activate the editing functionality by customizing associated forms and widgets





FIFTEEN

DOWNLOAD DEMO DATA

The tutorial is based on predefined data and QGIS 3.28.x LTR project downloadable from this link.

The .zip file contains the G3W-SUITE directory with three sub directories:

- projects: containing a QGIS project (buildings_management.qgs) already optimized for the tutorial
- project_data/spatialite: containing a SpatiaLite DB with basic data (build_management_demo. sqlite)
- plots: containing a a series of plots created with the DataPlotly plugin and saved in xml format



Inside the **build_management_demo.sqlite SpatiaLite DB** there are the following layers:

- buildings (polygon layer): reference layer for editing aspects
- **maintenance_works** (alphanumeric table): with the maintenance interventions associated with the individual buildings
- buildings_rating (alphanumeric table): with the annual assessments relating to individual buildings
- roads (linear layer): layer to define the address associated to any buildings
- work_areas (polygon layer): with the perimeter of work areas to be used to define any geo-constraints
- **type_subtype** (alphanumeric table): a decoding table of the type and subtype values associated with the individual buildings

IMPORTANT: a copy of this data are present on the server, you can not change your local data copy

The project (based on QGIS LTR 3.22.x) foresees:

- a dressing categorized by the buildings layer based on the categorical field type
- the presence of a 1: n relationship between the buildings layer and the alphanumeric maintenance_works and buildings_rating tables

- pre-developed **query forms** for the **buildings** layer and the **maintenance_works** table
- predefined editing widgets for the fields of the two main layers: buildings, maintenance_works and buildings_rating tables
- two standard print layout in A4 and A3 and an two atlas print layout based on buildgs layer features



15.1 Modify the QGIS project title

The publication system provides for the use of the title of the project as the unique identifier of the WebGis service.

So, before publishing the project, it will be NECESSARY to change the title associated with the basic project (Project -> Properties ... - Session: General)



SIXTEEN

ACCESS THE ONLINE SERVICE

To publish the project, you can **access the G3W-SUITE test application** via the following URL: https://v36.g3wsuite.it

To access the **Administration Panel** it is necessary to log in using the following credentials:

- user: demo
- password: G3wsuite!

In case of login fails, report the problem to info@gis3w.it

CHAPTER SEVENTEEN

PUBLISH THE QGIS PROJECT AS A WEBGIS SERVICE

After authentication it will be possible to access the **Administration session** and view the **Dashboard**.

In the Dashboard there will be the menu for access to the **Cartographic Groups** pertaining to your user and the menus relating to additional modules not active in this demo.

Click on the Show item in the ligth blue Groups box to acces at the list of available Cartographic Groups.

		💄 admin01	English	• 08
‡MENU	Dashboard Current situation			
🚯 Dashboard	🚯 Dashboard			
🔇 Cartographic groups 🗸 🗸	4			
+ Add group	4			
😵 Groups list	Groups			>
S Macro Cartographic groups <	Shov	w Ə		
₿ACL				
🚰 Users 🗸 🗸				
🛃 Add user				
醬 Users list				
+ Add group users				
🗮 Groups users list				
	Copyright © G3W-SUITE Version 3.1.dev-2020 2015 - 2020 GIS3W. All rights reserved.	01111110825: admini:	stration GIS app	plication.

Access the list of webgis in the Cartographic Group G3W-SUITE Demo clicking on the project number shown.

93W SUITE	=						🖶 Frontend	Å editor	Italiano 🔻
Emenu	Gruppi carto	grafici							🚯 Dashboard
😰 Scrivania	G3W-SUIT	E Demo							
 Gruppi cartografici 	Editing demo (CPSC	12857)							
ACL	ATA	-	cost (
뿔 Utenti 〈	2 Proge	etti 💿							
1LAW	-								
🔦 Normative 🛛 <									
ICDU									
🍄 Profili CDU 🤇 🤇									
_									_
g 3W _{SU}	JITE					🕷 Frontend	💄 admin01	Italia	ino 🝷 📽
I MENU		Progetti Pr	rojects list of grou	р		🍘 Dashboard 🚿 Gruppi	i cartografici 🚿 Lista	a progetti G	3w-Suite Demo
🚯 Scrivania									
		Group G3w-	Suite Demo 👁						
Gruppi cartografic	cı 🗸	Demo based on	n SpatiaLite data						
🕂 Aggiungi gruppo									
😧 Lista gruppi									
Macro Gruppi cart	tografici <	+ Progetto Q	igis 💽						
₿ACL		Tipo di prog	getto QGIS						
嶜 Utenti	<								
		Panoramica	Azioni	Logo	Titolo	Created/Modified			Widgets
I LAW		0		and the	Public buildings management - SpatiaLite	creato: Venerdì 03 A	prile 2020 21:20		
🔦 Normative	<		4			modificato: Martedì	07 Aprile 2020 15	:46	
ŧcdu			0						

Now click on the button to publish your **QGIS project**.

Fill out the form defining the various aspects to be associated with the WebGis service being published:

17.1 QGIS project

QGIS file: load the QGIS cartographic project to be published (.qgz or .qgs file)

17.2 ACL Users

Management of access permissions

- **Viewers users:** define the individual users (Viewers) who have the credentials to view the WebGis service. By choosing the anonymous user (**AnonymusUser**) the group will be freely accessible.
- **Viewer user groups:** you define the user groups (Viewer) which have the credentials to view the content of the service.

17.3 Default base layer

In this session you define which base layer should be active at startup.

The choice is limited to the list of base layers activated for the cartographic group in which you work.

It is also possible not to define any active base layer at startup.

17.4 Description data

- **Public title:** Title to be associated with the project and displayed on the client header. If left blank, the title associated with the QGIS project will be used or, in the absence of this, the name of the project file
- **Description:** Description of the project, it will appear at the public portal level.
- **Thumbnail (Logo):** logo to associate with the project. This image will be viewable in the list of projects within the cartographic group
- URL alias: a human readable URL for the map

ATTENTION: contents marked with * are mandatory.

17.5 Options and actions

Choose your preferred options regarding the following options:

- User QGIS project map start extent as webgis init extent: check this control if you want set initial extent from QGSI project initial extent, Project properties -> QGIS Server -> WMS capabilities (Advertised extent)
- Tab's TOC active as default: set tab's TOC (Layers, Base layers, Legend) open by default on startup of webgis service
- Legend position rendering: this option allows to set legend rendering position:
 - In a separate TAB: default value, the legend is rendered into a separate tab
 - Into TOC layers: the legend is rendered inside layers toc
- Automatic zoom to query result features: if in the results of a search there are only features of a layer, the webgis automatic zoom on their extension

QGIS projectPublic building management Spatialite	🏠 Dashboard > Cartographic groups > Projects list G3W-SUITE Demo > Update QGIS project g3w-suite-demo public building-management-spat
Shortcuts	
腳 Show map ↔ Show detail ☰ Layers	
敵 Qgis Project	ACL Users
Qgi file*	Editori user
Lick or Drag file to Upload	Set Editor Level 1 owner Editor2 user
project/g/aw-suitegastisilita.ags	Viewer users
	* (Anonymoustiser) * (viewer1) Editor user groups
	Viewer store straugs
N Default base layer	
Base Layer	
OSM (OpenStreetMap) v	
^b Description data	Options and actions
Public title	User DGIS project man start extent as webgis init extent
Official demo	Tab's TOC active as default*
Description	Layers
Ž* B <u>U</u> I B 14* A * Ξ Ξ Ξ* ⊞* ∞ X <> ∞ ?	Set tab's TOC open by default on init client
An example of cartographic management rich in analytical functions, researches, graphs and much more.	Legend position rendering*
To test the features and power of online editing, log in with the following credentials	In a separate TAB
user: viewer1 pwd: G3wsuite123	Set legend position rendering
	Automatic zoom to query result features
	Automatic zoom on query result features for only one layer
	Max feature to get for query*
	5
	Query control mode*
Thumbnail	Single
	Query by bbox control mode*
▲ Click or Drag file to Upload	Single
	Query by polygon control mode*
building.png	Single
JRL alias	
demo-34	
fou can set a human readable URL for the map. Only alphanumeric characters, not white space or special characters	
🖺 Save 🍎 Redo/Back	

After filling in the various form, click on the **Save button** to confirm your choices.

Save D Redo/Back

曲

If the publication was successful, the QGIS project will appear in the list of projects in the Cartographic Group.

Clicking on the **View map** icon will access the WebGis service in consultation.

G3W-Suite - G3w-Suite D Public buildings managemen	Demo nt - SpatlaLite				💄 admin0	1 Credits	😭 Home
🗟 Metadati	E Indirizzo Q	8 - 6 - 2/A - 2 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5	Risultati				
😝 Stampa							
Q Ricerche	Via Marcello Malpighi -> 0 -12 10		Buildings (1) 📩				-
🕰 Strumenti	andrea Mattioli 60	Convento dei Cappučcini		id Name	Address		_
💴 Марра	51 49 43		♀ ♣	10 Garibalo	di Palace Via Alfredo Oriani		
Strati Basi Legenda	249 743 120 118/C		General Info		Technical data		
U Tasto destro sui singoli layer per accedere alle funzionalità aggiuntive	Rio Eman	Uele 1193 114 5	Identification		Documents		
 Public buildings management - SpatiaLite Anthropic elements Roads 	36 34 32 36 R 22 R 8 29 27 25 21 Vie/GigMome		id	10 Garibaldi Palace	Photo	A.	
 ☑ Buildings Ⅲ Maintenance work 		Area 2 Vitoro Area	Address	Via Alfredo Oriani gia' Via Vecchia	Data sheet	Apri	
Work areas	Area 1	and a state of the	Туре	Residential	Link	Apri	
Gase map CTR multiscale	Br B Commence	Are Ashtanga 22 19 Juanta ang	Year of construction	n 2020	Categoria B		
	2 Leopoto 2 68 R 261	and the second sec					
	Piazza-Pietro-Bennado Via Giovanni F	Sel - Contraction - Sel	10 10				
	spoldo	aroni 30 × 28 9 × 24/4 1 × × × × × × × × × × × × × × × × × × ×	3				
	Rossi Luigi	43 minapana 446 23					
	A REAL RANGE	24 33 29 27 Via Gaspero p					
	Scuola Primaria	Via Gaspero Barbera					
	CopenStreetMap contributors.	Via Raffante 15 18 R Som					

EIGHTEEN

UPDATE THE PUBLISHED WEBGIS SERVICE

If you want to modify some graphic-functional aspects of your WebGis service, modify your QGIS project and update the WebGis service by clicking on the **Modify** icon

Reupload the QGIS project with your changes, click on the Save button and see the resuts on the cartographic client.

NINETEEN

ACTIVATION OF ADDITIONAL FUNCTIONS

Once your project has been published, you can access the list of widgets and additional functions to enrich your WebGis service.

19.1 Widget management

Though the **Layers list icon** it is possible to access the list of the geographical states that compose it and define some functional aspects that will be enabled at the cartographic client level.



The new session will show you the list of the layer present in the published QGIS project

QGIS Project Layers			🔀 Das	hboard > Cartographic grou	ups > Projects list G3W-SUITE Dem	D > Layer list QGIS project g3w-suite-de
Project Public building management	t Demo					
An example of cartographic manager To test the features and power of onl • user: viewer1 • pwd: G3wsuite123	ment rich in analytical functions, researches, graphs and much ine editing, log in with the following credentials	more.				
Show map Show detail Edit						
Data Structure						
Show 10 v entries					Sea	irch:
Label	Name	『 Type 』 WMS External	lt WFS 」:Actions		Download 11 capabilities	Not show attributes No If table If legend If
buildings	buildings ♥	/	° }	8 🛋 📮 🛛	Download	
Buildings rating	buildings_rating 👁	1	2		a Download	
Maintenance works	maintenance_works 🏾	1	2		∎ ▲ Download	
roads	roads 👁	/	° •	20 20 20 20 20 20 20 20 20 20 20 20 20 2	0 8 ≛Download	

- Label: layer alias applied at the QGIS project level
 - The eye icon allows you to know the ID associated with the layer at the project level, this ID will be useful for creating parameterized URLs
- Name: name of the layer (file or DB table)
 - **Type:** illustrates the type of data (WMS, PostGis, SpatiaLite, GDAL / OGR ...)
- WMS external: to speed up loading, the WMS layers present in a QGIS project are managed directly by Django and not by QGIS-Server. However, this method prevents the application of any styling (e.g. opacity level) defined at the project level. The choice of the external WMS option means that the WMS layer is managed directly by QGIS-Server and therefore the associated styling is applied.
- WFS: a check mark shows whether the layer is published as a WFS service or not
- Actions: a series of icons dedicated to various functions
 - evel

Caching Layer: allows you to activate and manage the cache of the single layer at the project

- Editing layer: shows if the online editing function is active on the layer and allows you to activate and define it
- 62
 - **Hide layer by user/groups:** hide specific layers from the TOC based on specific users or groups of users
- **QPlotly widget:** add or manage plots created with DataPlotly QGIS plugin



- **Geo-constraints by user/group:** create or manage editing and visualization geo-constraints based on poligonal layers
- • Alphanumeric and QGIS expressions constraints by user/groups: create or manage editing and visualization constraints based on SLQ language or QGIS expressions

- If Hide columns by User/Groups: create or manage constraints on one or more fields of a layer based on single or group user/s
- Widgets list: shows how many widgets (eg searches) are associated with this layer and allows you to activate new ones

2

- Manage layer styles: manage multi-style layer
- Not show attributes table: hide attributes table of the layer for every users
- No legend: it allows to define if the layer must have published the legend at TOC level of the WebGis client
- Download: allows the download of the geographic and not geographic layers in various formats
 - Download as shp/geotiff: for vector and raster layers
 - Download as GPK: for geographic or not geographic layers
 - Download as xls: for all types of layers, in .xls format
 - Download as csv: for all types of layers, in .csv format
 - Download as gpx: for geographic layers, in .gpx format

The number above each Action icon shows if and how many related objects are present.

Try to activate the available options and test the result on the WebGis

19.2 Search widget creation

To create a search tool available at WebGis level, choose the vector layer on which to apply the tool and click on the

Widget list icon 👎

NB: there may be a number of searches created by other users for the same layer.

You can activate them by clicking on the Linked chekbox.

Label	44	Name		.↓↑ Туре	IT WMS	External	IT WFS	11 A	tions			11	No legend ∥↑	Download as shp	II	Download as xls	11	Download as csv	n	Download as gpx	11
Buildi	ngs	buildi	ıgs	1			0		9 🛛	• •	ť	°									
	ØAd	d new wid	get																		
	Actio	ns						Name							Туре			Linked			
	/	•	Î					Like tes	t						search	1					
	1	•						Type ar	d volume						search	1					
	1	•	•					Differen	t from						search	1					
	1	•	Î.					Double	AND						search	1					

The listed searches can be modified, deleted or unlinked using the appropriate icons.

To create a new search, click on the blue link New widget.

In the related form we can define:

- Form Title
 - Type: "Search"
 - Name: name that G3W-SUITE will use to internally register the search widget.
- · General configuration of research and results

- Search title: title that will become available in the 'Research' panel of the WebGis interface

Search fields settings

- Field: field on which to carry out the research
- Widget: method of entering the value to be searched InputBox: manual compilation SelectBox: values shown via drop-down menu AutoCompleteBox: values shown through auto-complete mode
- Alias: alias assigned to the field that will appear in the search form
- Description: description assigned to the field
- Comparison operator: comparison operator (=, <,>,> <,> =, <=, LIKE, ILIKE) through which the search query will be carried out. The LIKE and ILIKE operators will only be available for PostGis or SpatiaLite layers
- Dependency: this parameter (optional) allows, only in the case of SelectBox widgets, to list the list of values of a field filtered according to the value defined for the previous fields. The tool allows, for example, to display, in the drop-down menu dedicated to the choice of cadastral particles, only the particles connected to the sheet chosen in the previous option. This function is only available for PostGis or SpatiaLite layers.

Now it is possible to define the dependence more or less strong (strictly).

In case of **strictly dependence**, the values of the dependent fields will be loaded **only after** the choice of the value of the field on which the dependency depends.

Otherwise it will be possible to define the values of the individual fields freely and **without a specific order**. The values available for the other fields will in any case depend on the choice made.

🕂 Add

The button allows you to add additional fields for the construction of the search query currently manageable through **AND/OR operators**.

The example below shows the compilation of the form for creating a search widget dedicated to a cadastral cartography layer.

pe*		Name*		
Search		✓ Type an	d year	
General configura	ation for se	arch widget and re	sults	
earch title				
Type and year				
lient search title iden	tification			
earch field settir	ngs			2
ield		Widget	Alias	Description
type	~	SelectBox 🗸	Туре	
			Alias field name for client search	
			input	
omparison operator			input	
omparison operator = (equal)	~		input	
omparison operator = (equal) ependency	~		input	
Comparison operator = (equal) Dependency 	~	AND	input v	
Comparison operator = (equal) bependency Search field setti	v v	AND	input	
Comparison operator = (equal) Dependency Search field settin	v v	AND	input v	Description
Comparison operator = (equal) Dependency Search field settin Field year	v v ngs	AND Widget SelectBox V	input Alias Year	Description
Comparison operator = (equal) Dependency Search field settin Field year	r v ngs	AND Widget SelectBox ~	Allas Year Allas field name for client search input	Description
Comparison operator = (equal) bependency Search field settlin rield year Comparison operator	ngs	AND Widget SelectBox V	Input Input Vear Allas field name for client search input	Description
Comparison operator = (equal) Bependency Search field settlin Field year Comparison operator = (equal)	r v	AND Widget SelectBox ~	Input	Description
Comparison operator = (equal) Dependency Search field settin rield year = (equal) Dependency	r v	AND Widget SelectBox ~ Strictly dependent	Input	Description

Once the form has been filled in, click on the **OK button to save** the settings.

Once the settings are saved, the created widget will appear in the list of Widgets associated with the layer.

The widget will already be linked and therefore available in the WebGis interface on the left panel.



19.3 Plots widget

Add plots created using QGIS DataPlotly (a great plugin developed by Matteo Ghetta) in the cartographic client.

The module, based on the Plotly library, manages plots saved as xml.

The plots are connected to the layers defined on the QGIS project, in this way, as for the searches and the constraints, it is possible to activate the same plots on all WebGis services in which the reference layer is present.

For this reason, there may be some plots created by other users for the same layer. You can activate them by **clicking on the Linked chekbox**.

Label	11 Name	↓† Type ↓† WMS External ↓† WFS ↓† Ac	tions 4	No † legend ↓† sl	Download as	Download as gpkg	Download as	Download as csv	Download as
Buildings	buildings 👁	/	€ Ø % 📥 T ¢ Ø		3				
0	New qplotly widget								
Act	ions	Active on startup	Title		Туре	Fron	project	L	inked
	/ 📋 🚸	•	Type distribution		pie			6	2
	/ 💼 🐵		High- Year by type		bar				2
	/ 📋 📣		Year - Volume		scatter				2

The title of the chart, defined at the plugin level, will be the unique identifier.

Try to create your plots in the QGIS project, save them as .xml and upload them to view the resluts on the webgis.





The graphs are filterable based on the:

- ^e features visible on the map
- T filter based on the selected features

These filters are also reflected on the plots associated to the related data (in 1:N mode) based on the visible and/or selected parent features.

The **filter based on the map content** can be activated globally on all plots (icon at the top of the panel dedicated to charts) or on only some specific plots (icon placed at the level of the individual plots).

The plots will automatically update after pan and zoom operations on the map

If activated, the **filter based on the selected features** is automatically activated on all related plots (associated with the same layer and with the 1:N relationed tables)

Appropriate messages at the single plots level will indicate the activation of these filters.

If 1: N relationships are associated with the interrogated layer and plots have been activated on the referencing tables, it will also be possible to consult these plots by querying the referenced layer and clicking on the **Show relation charts** icon present in the results form.

uildings	(1)			E -
		ID	Name	Address
# ₩ ₽	±∎⊘∂	4	G3WSUITE	Via Giov
General i	nfo Teo dat	hnical a	Relatio	ns
Identificat	tion	Docume	ents	
Identificat	tion 4	Docume	ents	
Identificat ID Name	tion 4 G3WSUITE	Docume	ents	
Identificat ID Name Address	tion 4 G3WSUITE Via Giovanni Lampredi	Docume Photo Form	ents Dpe	

Show relation charts: display of graphs related to 1: N related data. Only if 1: N relationships are associated with the interrogated layer and graphics have been activated on the boy tables.

TWENTY

EDITING ON LINE

Forms and editing widgets are already defined on the project associated with the tutorial for the geometric layer of buildings and for the alphanumeric table related interventions_maintenance.

- Buildings
 - id (integer primary key): autogenerate
 - name (text NOT NULL): text edit
 - address (text): Value relation (roads layer code/name fileds)
 - zone (text): text edit (with default values based on a QGIS expression to for association with the intersecting works area)
 - type (text NOT NULL): unique values (Administrative, Commercial, Residential)
 - subtype (text NOT NULL): value relation (based on type_subtype table for a drill-down cascading forms)
 - **attachment** (integer): check box 1/0 (the visibility of the conditional form Documents is based on this field)
 - **photo** (text): attachment
 - link (text): text edit
 - form (text): attachment
 - user (text): text edit (automatically filled in with the G3W-SUITE username creator of the feature)
 - year (integer NOT NULL): unique values (2015,2016,2017,2018,2019,2020)
 - high (integer NOT NULL): range (10-30 step 2)
 - volume (integer): range (50-200 step 10)
 - surface (integer): text edit
 - architectural_barriers (text): Checkbox (Checked Not checked)
 - date_barriers (date): date (yyyy/MM/dd)
 - safety_exits (text): checkbox (Checked Not checked)
 - date_exits (date): date (yyyy/MM/dd)
 - fire_system (text): Checkbox (Checked Not checked)
 - date_fire (date): date (yyyy/MM/dd)
- Maintenance_works
 - id (integer primary key): autogenerate

- id_buildings (text relation key): text edit
- maintenance (text NOT NULL): unique values
- date (date): date (yyyy/MM/dd)
- form (text): attachment
- value (integer): range (10-30 step 2)
- outcome (text): unique values (good, medium, bad)
- **responsible** (text): text edit
- cost (integer): range (1000-5000 step 1)
- validation (boolean): checkbox (0/1)
- Buildings rating
 - id (integer primary key): autogenerate
 - id_buildings (text relation key): text edit
 - date (date): date (yyyy/MM/dd)
 - value (integer): range (1000-4000 step 500)
 - year (integer): range (2018-2022 step 1)

To activate the editing function on webgis, access the list of layers and identify the three layers shown above.

QGIS Project Layers			Bashboard ⇒ Cartogra	phic groups 🚿 Pr	rojects list G3W-SUITE Demo	Layer list QGIS project g3w-suite-dem
Project						
Public building r An example of cartog To test the features a • user: viewer1 • pwd: G3wsuit	management Demo graphic management rich in analytical functions, researches, g und power of online editing, log in with the following credentia 	raphs and much more. Is				
節 Show map Show detail Ed	ist and the second s					
Data Structure						
Show 10 v entries					Search	h:
Label	👫 Name	』: Type 』: WMS Extern	al 🕼 WFS 🏦 Actions	I	Download	Not show attributes No table 🕼 legend 🍂
buildings	buildings 👁	/	° § 2 2 2 4	ti 🕈 🛗 🗳	▲ Download	• •
Buildings rating	buildings_rating 👁	1	☑ 쓸 🕍 🦿 🗒	8 2	🛓 Download	•
Maintenance works	maintenance_works @	1	☑ 營 📥 📍 🖩	• 2	🛓 Download	• •
roads	roads 👁		° € 2 2 1 1	b Y ⊞ \$	≛ Download	

Clicking on the icon **Editing layer** (placed at the left of each rows) will open a modal window that will allow you to:

- define the editing activation scale (only for geometric tables)
- define the Viewer users (individuals or groups) enabled for online editing

With regard to the last aspect, it should be noted that **Viewers users** (individuals or groups) **available** in the drop-down menu **will be limited to those who have allowed access in consultation to the WebGis project**

Activation	layer_ed	iting		×
Check on unc	heck to atti	ve/deactive editing layer o	apabilities:	
Scale				
2500				0
Scale after tha	t editing m	ode is active		
User adding o	lata field			
user				Ψ.
Optional: sele Value stored i	ct layer fiel nto the field	d to store username that e I it will be so structured: [i	entered the data. Showed only username]	string field.
User editing	data field			
				Ŧ
Optional: sele Value stored i	ct layer fiel nto the field	d to store username that u I it will be so structured: [i	updated the data. Showed onl username]	y string field.
Select viewers	s with 'view	permission' on project th	at can edit layer:	
× (viewer)	.)			
Select user wi	th viewer n	ole can do editing on layer		
User	Add	Update geometry	Update attributes	Delete
(viewer1)				
User viewer §	roups			
Select VIEWER	groups ca	n do editing on layer		
			* 0	lose 🗸 Ok

Once the editing function is activated, updating the service, the Tools menu will appear on the left panel.

By activating the editing function it will be possible to edit the geometries and attributes of the Public Buildings layer and the related interventions.



eral info *			Technical data *		
ntification *			Documents		
ID*			Photo		
Name*	Pink building			casa-danzante-praga.jpg	
Address \ominus	Piazza Pietro Leopoldo	¥	Form		
Zone (QGIS expression)				building_detection_card.pdf	
			Link	https://g3wsuite.it	
Туре *	Residential	-			
Subtype		*	User/Date last modification		
Documents to be attached	✓ 1				
tions					
MAINTENANCE WORKS		(2 RATING		

For further information on the web editing function, read the dedicated chapter on the manual

TWENTYONE

PERSONALIZE YOUR DEMO

Do you want to test the online editing function more deeply?

Redefine attribute forms, aliases and editing widgets associated with the individual fields and reload the project to check the new settings.

It is advisable to consult the paragraph dedicated to the list and limitations of the individual editing widgets inheritable from the QGIS project.